

Power MOSFET Selection Guide

2003

MOSFETs

computer
power supply
consumer
automotive
communications
industrial

The Power Franchise™



F

AIRCHILD

SEMICONDUCTOR®

Across the board. Around the world.™

FAIRCHILD
SEMICONDUCTOR®

Analog Discrete Interface & Logic Optoelectronics

Power MOSFET Selection Guide

2003

Table of Contents

Product	page	Product	page
BGA N-Channel	1	TO-252 (DPAK) N-Channel	13
BGA P-Channel	1	TO-252 (DPAK) P-Channel	16
SC70-6 N-Channel	1	DIP-8 Complementary N- and P-Channel	17
SC70-6 Complementary N- and P-Channel	1	TO-220 N-Channel	17
SC70-6 P-Channel	2	TO-220 P-Channel	22
SC75-6 FLMP P-Channel	2	TO-262 (I ² PAK) N-Channel	22
SuperSOT™-3/SOT-23 N-Channel	2	TO-262 (I ² PAK) P-Channel	24
SuperSOT™-3/SOT-23 P-Channel	2	TO-263 (D ² PAK) N-Channel	25
MicroFET™ N-Channel	3	TO-263 (D ² PAK) P-Channel	29
MicroFET™ P-Channel	3	TO-220F N-Channel	30
SuperSOT™-6/TSOP-6 FLMP N-Channel	3	TO-220F P-Channel	33
SuperSOT™-6/TSOP-6 FLMP P-Channel	3	TO-247 N-Channel	34
SuperSOT™-6/TSOP-6 N-Channel	3	TO-3P N-Channel	34
SuperSOT™-6/TSOP-6 Complementary N- and P-Channel ..	3	TO-3P P-Channel	35
SuperSOT™-6/TSOP-6 P-Channel	4	TO-3PF N-Channel	36
TSSOP-8 N-Channel	4	TO-3PF P-Channel	37
TSSOP-8 Complementary N- and P-Channel	4	TO-264 N-Channel	37
TSSOP-8 P-Channel	5	Special Function Products	
SuperSOT™-8 N-Channel	5	Application Specific	
SuperSOT™-8 Complementary N- and P-Channel	5	SC70-5	38
SuperSOT™-8 P-Channel	5	SuperSOT™-6/TSOP-6	38
SO-8 FLMP N-Channel	5	Load Switches	
SO-8 FLMP P-Channel	6	SC70-6 P-Channel	38
SO-8 N-Channel	6	SuperSOT™-6/TSOP-6 P-Channel	38
SO-8 Complementary N- and P-Channel	8	SuperSOT™-8 P-Channel	38
SO-8 P-Channel	8	MOSFET & Schottky Diode Combo	
TO-92 N-Channel	9	SuperSOT™-6/TSOP-6 P-Channel	38
SOT-223 N-Channel	9	TSSOP-8™ P-Channel	38
SOT-223 P-Channel	10	SO-8 N-Channel	38
SO-14 N-Channel	10	SO-8 P-Channel	38
TO-92L N-Channel	10		
TO-251 (IPAK) N-Channel	10		
TO-251 (IPAK) P-Channel	12		

Note:

Unless otherwise specified,

Q_G is given @ 5V_{GS} for MOSFETs with ratings of 30V_{DS} and below.

Q_G is given @ 10V_{GS} for MOSFETs with ratings higher than 30V_{DS}.

Products	BV _{DSS} Min (V)	Configuration	R _{DS(ON)} Max. (Ohms) @ V _{GS} =				Q _g (nC) Typ @ V _{GS} = 5V (Note pg. i)	Maximum Rating				
			10V	4.5V	2.5V	1.8V		I _D (A)	P _D (W)			
BGA N-Channel												
1.5x1.5 mm												
FDZ298N	20	Single	-	0.027	0.039	-	7	6	1.7			
2.0x2.0 mm												
FDZ203N	20	Single	-	0.018	0.03	-	11	7.5	1.6			
2.0x2.5 mm												
FDZ201N	20	Single	-	0.018	0.03	-	11	9	2			
FDZ209N	60	Single	-	0.08@5V	-	-	6.3	4	2			
2.5x4.0 mm												
FDZ2553N	20	Monolithic (Common Drain)	-	0.014	0.02	-	12	9.6	2.1			
FDZ2553NZ	20	Monolithic (Common Drain)	-	0.014	0.02	-	13	9.6	2.1			
FDZ2551N	20	Monolithic (Common Drain)	-	0.018	0.03	-	11	9	2.1			
3.5x4.0 mm												
FDZ7064N	30	Single	0.007	0.008	-	-	31	13.5	2.2			
FDZ7064S	30	SyncFET™	0.0072	0.0088	-	-	25	13.5	2.2			
5.0x5.5 mm												
FDZ5047N	30	Single	0.0029	0.0045	-	-	52	22	2.8			
BGA P-Channel												
1.5x1.5 mm												
FDZ299P	-20	Single	-	0.055	0.08	-	6.6	4.6	1.7			
2.0x2.0 mm												
FDZ204P	-20	Single	-	0.045	0.075	-	9	4.5	1.8			
2.0x2.5 mm												
FDZ202P	-20	Single	-	0.045	0.075	-	9	5.5	2			
2.5x4.0 mm												
FDZ2554P	-20	Monolithic (Common Drain)	-	0.028	0.045	-	14	6.5	2.1			
FDZ2554PZ	-20	Monolithic (Common Drain)	-	0.028	0.045	-	15	6.5	2.1			
FDZ2552P	-20	Monolithic (Common Drain)	-	0.045	0.075	-	9	5.5	2.1			
3.5x4.0 mm												
FDZ208P	-30	Single	0.0105	0.0165	-	-	25	12.5	2.2			
FDZ206P	-20	Single	-	0.0095	0.0145	-	38	13	2.2			
SC70-6 N-Channel												
FDG6335N	20	Dual	-	0.3	0.4	-	1.1	0.7	0.3			
FDG327N	20	Single	-	0.09	0.1	0.14	4.5	1.5	0.42			
FDG327NZ	20	Single	-	0.09	0.1	0.14	4.2	1.5	0.42			
FDG329N	20	Single	-	0.09	0.115	-	3.3	1.5	0.42			
FDG311N	20	Single	-	0.115	0.15	-	3	1.9	0.75			
FDG6303N	25	Dual	-	0.45	0.6@2.7V	-	1.64	0.5	0.3			
FDG6301N	25	Dual	-	4	5@2.7V	-	0.29	0.22	0.3			
FDG313N	25	Single	-	0.45	0.6@2.7V	-	1.64	0.95	0.75			
FDG315N	30	Single	0.12	0.16	-	-	2.1	2	0.75			
FDG361N	100	Single	0.5	-	-	-	3.7	0.6	0.42			
SC70-6 Complementary N- and P-Channel												
FDG6332C	20	Complementary	-	0.3	0.4	-	1.1	0.7	0.3			
	-20			0.42	0.63		1.4	0.6				
FDG6321C	25	Complementary	-	0.45	0.6@2.7V	-	1.64	0.5	0.3			
	-25			1.1	1.5@2.7V		1.1	0.41				
FDG6320C	25	Complementary	-	4	5@2.7V	-	0.29	0.22	0.3			
	-25			10	13@2.7V		0.22	0.14				

Products	BV_{DSS} Min (V)	Configuration	$R_{DS(ON)}$ Max. (Ohms) @ $V_{GS} =$				Q_g (nC) Typ @ $V_{GS} = 5V$ (Note pg. i)	Maximum Rating	
			10V	4.5V	2.5V	1.8V		I_D (A)	P_D (W)
SC70-6 Complementary N- and P-Channel (cont.)									
FDG6322C	25 -25	Complementary	-	4	5@2.7V	-	1.1	0.22	0.3
SC70-6 P-Channel									
FDG316P	-30	Single	0.19	0.3	-	-	3.5	1.6	0.75
FDG6304P	-25	Dual	-	1.1	1.5@2.7V	-	1.1	0.41	0.3
FDG6302P	-25	Dual	-	10	13@2.7V	-	0.22	0.14	0.3
FDG314P	-25	Single	-	1.1	1.5@2.7V	-	1.1	0.65	0.75
FDG6308P	-20	Dual	-	0.4	0.55	0.8	1.8	0.6	0.3
FDG6306P	-20	Dual	-	0.42	0.63	-	1.4	0.6	0.3
FDG6318P	-20	Dual	-	0.78	1.2	-	0.86	0.5	0.3
FDG6318PZ	-20	Dual	-	0.78	1.2	-	1.08	0.5	0.3
FDG326P	-20	Single	-	0.14	0.18	0.25	4.4	1.5	0.75
FDG318P	-20	Single	Use FDG328P						
FDG328P	-20	Single	-	0.145	0.21	-	3.7	1.5	0.75
FDG312P	-20	Single	-	0.18	0.25	-	3.3	1.2	0.75
FDG6316P	-12	Dual	-	0.27	0.36	0.65	1.7	0.7	0.3
FDG330P	-12	Single	-	0.11	0.15	0.215	5	2	0.75
SC75-6 FLMP P-Channel									
FDJ129P	-20	Single	-	0.07	0.12	-	4	4.2	1.6
SuperSOT-3/SOT-23 N-Channel									
FDN339AN	20	Single	-	0.035	0.05	-	7	3	0.5
FDN371N	20	Single	-	0.05	0.06	-	7.6	2.5	0.5
FDN327N	20	Single	-	0.07	0.08	0.12	4.5	2	0.5
FDN335N	20	Single	-	0.07	0.1	-	3.5	1.7	0.5
NDS335N	20	Single	-	0.11	0.14@2.7V	-	6.4	1.7	0.5
NDS331N	20	Single	-	0.16	0.21@2.7V	-	3.5	1.3	0.5
FDV305N	20	Single	-	0.22	0.3	-	1.1	0.9	0.35
FDV303N	25	Single	-	0.45	0.6@2.7V	-	1.64	0.68	0.35
FDV301N	25	Single	-	4	5@2.7V	-	0.49	0.22	0.35
FDN359AN	30	Single	0.046	0.06	-	-	5	2.7	0.5
FDN337N	30	Single	-	0.065	0.082	-	7	2.2	0.5
FDN357N	30	Single	0.06	0.09	-	-	4.2	1.9	0.5
NDS355AN	30	Single	0.085	0.125	-	-	3.5	1.7	0.5
NDS355N	30	Single	Use NDS355AN						
FDN361AN	30	Single	0.1	0.15	-	-	2.1	1.8	0.5
NDS351AN	30	Single	0.16	0.25	-	-	1.9	1.2	0.5
NDS351N	30	Single	Use NDS351AN						
FDN372S	30	SyncFET	0.04	0.05	-	-	5.8	2.6	0.5
BSS138	50	Single	3.5	6	-	-	1.7	0.22	0.36
FDN5630	60	Single	0.1	-	-	-	7	1.7	0.5
2N7002MTF	60	Single	5	-	-	-	-	0.115	0.2
MMBF170	60	Single	5	-	-	-	1.7	0.5	0.3
NDS7002A	60	Single	2	3	-	-	1.7	0.28	0.3
2N7000	60	Single	5	5.3	-	-	1.7	0.2	0.4
2N7002	60	Single	7.5	7.5	-	-	1.7	0.12	0.2
BSS123	100	Single	6	-	-	-	1.4	0.17	0.36
SuperSOT-3/SOT-23 P-Channel									
NDS0605	-60	Single	5	-	-	-	1.8	0.18	0.36
FDN5618P	-60	Single	0.17	0.23	-	-	8.6	1.2	0.5
NDS0610	-60	Single	10	20	-	-	1.8	0.12	0.36
BSS84	-50	Single	10	-	-	-	0.9	0.13	0.36
FDN360P	-30	Single	0.03	0.125	-	-	6.2	2	0.5
NDH8502P	-30	Single	Use FDN360P						
FDN358P	-30	Single	0.125	0.2	-	-	4	1.5	0.5
NDS356AP	-30	Single	0.2	0.3	-	-	3.4	1.1	0.5

Products	BV _{DSS} Min (V)	Configuration	R _{DS(ON)} Max. (Ohms) @ V _{GS} =				Q _g (nC) Typ @ V _{GS} = 5V (Note pg. i)	Maximum Rating	
			10V	4.5V	2.5V	1.8V		I _D (A)	P _D (W)
SuperSOT-3/SOT-23 P-Channel (cont.)									
NDS356P	-30	Single	Use NDS356AP						
NDS352AP	-30	Single	0.3	0.5	-	-	2	0.9	0.5
NDS352P	-30	Single	Use NDS352AP						
FDV304P	-25	Single	-	1.1	1.5@2.7V	-	1.1	0.46	0.35
FDV302P	-25	Single	-	10	13@2.7V	-	0.22	0.12	0.35
FDN304P	-20	Single	-	0.052	0.07	0.1	12	2.4	0.5
FDN304PZ	-20	Single	-	0.052	0.07	0.1	12	2.4	0.5
FDN302P	-20	Single	-	0.055	0.08	-	9	2.4	0.5
FDN340P	-20	Single	-	0.07	0.11	-	8	2	0.5
FDN342P	-20	Single	-	0.08	0.13	-	6.3	2	0.5
FDN338P	-20	Single	-	0.115	0.155	-	4.4	1.6	0.5
FDN308P	-20	Single	-	0.125	0.19	-	3.8	1.5	0.5
FDN336P	-20	Single	-	0.2	0.27	-	3.6	1.2	0.5
NDS332P	-20	Single	-	0.3	0.41@2.7V	-	3.7	1	0.5
FDN306P	-12	Single	-	0.04	0.05	0.08	12	2.6	0.5
MicroFET N-Channel									
FDM3300NZ	20	Dual (Common Drain)	-	0.023	0.028	-	12	10	2.5
MicroFET P-Channel									
FDM606P	-20	Single	-	0.026	0.033	0.052	20	6.8	1.92
SuperSOT-6/TSOP-6 FLMP N-Channel									
FDC796N	30	Single	0.009	0.012	-	-	14	12.5	1.8
FDC3616N	100	Single	0.07	-	-	-	23	3.7	1.8
SuperSOT-6/TSOP-6 FLMP P-Channel									
FDC6036P	-20	Dual	-	0.044	0.064	0.095	10	5	1.5
FDC697P	-20	Single	-	0.02	0.025	0.035	39	8	1.9
FDC699P	-20	Single	-	0.022	0.03	-	27	7	1.9
SuperSOT-6/TSOP-6 N-Channel									
FDC6401N	20	Dual	-	0.07	0.095	-	3.3	3	0.96
FDC6305N	20	Dual	-	0.08	0.12	-	3.5	2.7	0.9
FDC637AN	20	Single	-	0.024	0.032	-	10.5	6.2	1.6
NDH831N	20	Single	Use FDC637AN						
FDC6303N	25	Dual	-	0.45	0.6@2.7V	-	1.64	0.68	0.9
FDC6301N	25	Dual	-	4	5@2.7V	-	0.49	0.22	0.9
FDC6561AN	30	Dual	0.095	0.145	-	-	2.1	2.5	0.9
FDC645N	30	Single	0.026	0.03	-	-	13	5.5	1.6
FDC655AN	30	Single	0.027	0.035	-	-	9	6.3	1.6
FDC633N	30	Single	-	0.042	0.054	-	11	5.2	1.6
FDC653N	30	Single	0.035	0.055	-	-	12	5	1.6
NDC651N	30	Single	0.06	0.09	-	-	10	3.2	1.6
NDC7002N	50	Dual	2	-	-	-	1	0.51	0.96
FDC5612	60	Single	0.055	-	-	-	12.5	4.3	1.6
FDC3512	80	Single	0.077	-	-	-	13	3	1.6
FDC3601N	100	Dual	0.5	-	-	-	3.7	1	0.96
FDC3612	100	Single	0.125	-	-	-	14	2.6	1.6
FDC2512	150	Single	0.425	-	-	-	8	1.4	1.6
FDC2612	200	Single	0.725	-	-	-	8	1.1	1.6
SuperSOT-6/TSOP-6 Complementary N- and P-Channel									
FDC6420C	20	Complementary	-	0.07	0.095	-	3.3	3	0.96
	-20			0.125	0.19		3.7	2.2	
FDC6327C	20	Complementary	-	0.08	0.12	-	3.25	2.7	0.96
	-20			0.17	0.25		2.85	1.9	
FDC6320C	25	Complementary	-	-	5@2.7V	-	0.29	0.22	0.9
	-25				13@2.7V		0.23	0.12	

Products	BV _{DSS} Min (V)	Configuration	R _{DS(ON)} Max. (Ohms) @ V _{GS} =				Q _g (nC) Typ @ V _{GS} = 5V (Note pg. i)	Maximum Rating	
			10V	4.5V	2.5V	1.8V		I _D (A)	P _D (W)
SuperSOT-6/TSOP-6 Complementary N- and P-Channel (cont.)									
FDC6322C	25 -25	Complementary	-	-	5@2.7V 1.5@2.7V	-	0.49 1	0.22 0.46	0.9
FDC6321C	25 -25	Complementary	-	0.45 1.1	-	-	1.64 1.1	0.68 0.46	0.9
FDC6432SH	30 -12	Complementary	0.09	0.105	0.125	0.22	2.5 5.7	2.4 -2.5	1.3
FDC6333C	30 -30	Complementary	0.095 0.15	0.15 0.22	-	-	4.7 4.1	2.5 2	0.96
NDC7001C	60 -60	Complementary	2 5	4 7.5	-	-	1.1 1.6	0.51 0.34	0.96
SuperSOT-6/TSOP-6 P-Channel									
NDC7003P	-60	Dual	5	7	-	-	1.6	0.34	0.96
FDC5614P	-60	Single	0.105	0.135	-	-	15	3	1.6
FDC6506P	-30	Dual	0.17	0.28	-	-	2.3	1.8	0.96
FDC658P	-30	Single	0.05	0.075	-	-	8	4	1.6
FDC654P	-30	Single	0.075	0.125	-	-	6.2	3.6	1.6
NDC652P	-30	Single	0.11	0.18	-	-	10.5	2.4	1.6
FDC6304P	-25	Dual	-	1.1	1.5@2.7V	-	1.1	0.46	0.9
FDC6302P	-25	Dual	-	10	13@2.7V	-	0.22	0.12	0.9
FDC6312P	-20	Dual	-	0.115	0.155	0.225	4.4	2.3	0.96
FDC6310P	-20	Dual	-	0.125	0.19	-	3.7	2.2	0.96
FDC6306P	-20	Dual	-	0.17	0.25	-	3	1.9	0.96
FDC6308P	-20	Dual	Use FDC6306P						
FDC604P	-20	Single	-	0.033	0.043	0.06	19	5.5	1.6
FDC602P	-20	Single	-	0.035	0.05	-	14	5.5	1.6
FDC638P	-20	Single	-	0.048	0.065	-	10	4.5	1.6
FDC640P	-20	Single	-	0.053	0.08	-	9	4.5	1.6
FDC642P	-20	Single	-	0.065	0.1	-	7.2	4	1.6
FDC634P	-20	Single	-	0.08	0.11	-	7.2	3.5	1.6
FDC636P	-20	Single	-	0.13	0.18	-	6	2.8	1.6
FDC6318P	-12	Dual	-	0.09	0.125	0.2	5.4	2.5	0.96
FDC606P	-12	Single	-	0.026	0.035	0.053	18	6	1.6
TSSOP-8 N-Channel									
FDW2501NZ	20	Dual	-	0.018	0.025	-	12	5.5	1
FDW2501N	20	Dual	-	0.018	0.028	-	14	6	1
FDW2503NZ	20	Dual	-	0.02	0.026	-	12	5.5	1
FDW2503N	20	Dual	-	0.021	0.035	-	12	5.5	1
FDW9926A	20	Dual	-	0.032	0.045	-	6	4.5	1
FDW2507N	20	Dual (Common Drain)	-	0.019	0.023	-	20	7.5	1.6
FDW2507NZ	20	Dual (Common Drain)	-	0.019	0.023	-	20	7.5	1.6
FDW2509NZ	20	Dual (Common Drain)	-	0.02	0.026	-	13	7.1	1.6
FDW2515NZ	20	Dual (Common Drain)	-	0.029	0.04	-	9	5.8	1.6
FDW2516NZ	20	Dual (Common Drain)	-	0.03	0.04	-	9	5.8	1.6
TSSOP-8 Complementary N- and P-Channel									
FDW2520C	20 -20	Complementary	-	0.018 0.035	0.028 0.057	-	14 14	6 4.4	1
FDW2521C	20 -20	Complementary	-	0.021 0.043	0.035 0.07	-	12 9.7	5.5 3.8	1

Products	BV _{DSS} Min (V)	Configuration	R _{DS(ON)} Max. (Ohms) @ V _{GS} =				Q _g (nC) Typ @ V _{GS} = 5V (Note pg. i)	Maximum Rating	
			10V	4.5V	2.5V	1.8V		I _D (A)	P _D (W)
TSSOP-8 P-Channel									
FDW256P	-30	Single	0.0135	0.02	-	-	28	8	1.3
FDW2506P	-20	Dual	-	0.022	0.033	-	21	5.3	1
FDW2502P	-20	Dual	-	0.035	0.057	-	14	4.4	1
FDW2502PZ	-20	Dual	-	0.035	0.057	-	14	4.4	1
FDW2504P	-20	Dual	-	0.043	0.07	-	9.7	3.8	1
FDW254P	-20	Single	-	0.012	0.015	0.0215	60	9.2	1.3
FDW254PZ	-20	Single	-	0.012	0.015	0.0215	60	9.2	1.4
FDW252P	-20	Single	-	0.0125	0.018	-	41	8.8	1.3
FDW262P	-20	Single	-	0.047	0.065	0.1	13	4.5	1.3
FDW2508P	-12	Dual	-	0.018	0.022	0.03	26	6	1.3
FDW258P	-12	Single	-	0.011	0.014	0.02	61	9	1.3
SuperSOT-8 N-Channel									
FDR8305N	20	Dual	-	0.022	0.028	-	16.2	4.5	0.8
FDR6580	20	Single	-	0.009	0.011	-	34	11.2	1.8
FDR6674A	30	Single	0.0085	0.0095	-	-	33	11.5	1.8
FDR4420A	30	Single	0.009	0.013	-	-	23	11	1.8
FDR6678A	30	Single	0.02	0.024	-	-	13	7.5	1.8
SuperSOT-8 Complementary N- and P-Channel									
FDR8702H	20	Complementary	-	0.038	0.054	-	7	3.6	0.8
	-20		-	0.08	0.11	-	6	-2.6	
SuperSOT-8 P-Channel									
FDR8508P	-30	Dual	0.05	0.075	-	-	8	3	0.8
FDR856P	-30	Single	Use FDR858P						
FDR858P	-30	Single	0.019	0.028	-	-	21	8	1.8
FDR8308P	-20	Dual	-	0.05	0.07	-	13	3.2	0.8
NDH8302P	-20	Dual	Use NDH8304P						
NDH8304P	-20	Dual	-	0.07	0.095@2.7V	-	16	2.7	0.8
FDR844P	-20	Single	-	0.011	0.014	0.02	53	10	1.8
FDR840P	-20	Single	-	0.011	0.016	-	41	10	1.8
FDR836P	-20	Single	Use FDR838P						
FDR838P	-20	Single	-	0.017	0.024	-	30	8	1.8
NDH834P	-20	Single	Use FDR838P						
NDH832P	-20	Single	-	0.06	0.08@2.7V	-	18	4.2	1.8
FDR842P	-12	Single	-	0.009	0.012	0.016	57	11	1.8
SO-8 FLMP N-Channel									
FDS6064N7	20	Single	-	0.0035	0.004	0.006	70	23	3
FDS7062N7	20	Single	Use FDS6064N7						
FDS6162N7	20	Single	-	0.0035	0.005	-	52	23	3
FDS6064N3	20	Single	-	0.004	0.005	0.007	70	23	3
FDS6162N3	20	Single	-	0.0045	0.006	-	52	21	3
FDS7064N7	30	Single	-	0.007	-	-	30	16.5	3
FDS7064N	30	Single	-	0.0075	-	-	30	16	3
FDS7088N7	30	Single	0.003	0.004	-	-	37	23	3
FDS7088N3	30	Single	0.004	0.0055	-	-	34	21	3
FDS7066N7	30	Single	0.0045	0.0055	-	-	43	23	3
FDS7060N7	30	Single	0.005	0.007	-	-	35	19	3
FDS7066N3	30	Single	0.0055	0.0065	-	-	43	23	3
FDS7082N3	30	Single	0.006	0.008	-	-	38	17.5	3
FDS7096N3	30	Single	0.009	0.012	-	-	16	14	3
FDS7066SN3	30	SyncFET	0.0055	0.006	-	-	41	19	3
FDS7064SN3	30	SyncFET	0.008	0.0095	-	-	25	16	3.13
FDS4070N7	40	Single	0.007	-	-	-	47	15.3	3
FDS4070N3	40	Single	0.0075	-	-	-	47	15.3	3
FDS4072N7	40	Single	0.009	0.011	-	-	33	12.4	3
FDS4080N7	40	Single	0.01	-	-	-	30	13	3.9

Products	BV _{DSS} Min (V)	Configuration	R _{DS(ON)} Max. (Ohms) @ V _{GS} =				Q _g (nC) Typ @ V _{GS} = 5V (Note pg. i)	Maximum Rating	
			10V	4.5V	2.5V	1.8V		I _D (A)	P _D (W)
SO-8 FLMP N-Channel (cont.)									
FDS4072N3	40	Single	0.01	0.012	-	-	33	12.4	3
FDS4080N3	40	Single	0.0105	-	-	-	30	13	3.9
FDS5170N7	60	Single	0.012	-	-	-	51	10.6	3
FDS3170N7	100	Single	0.026	-	-	-	55	6.7	3
FDS2070N3	150	Single	0.078	-	-	-	38	4.1	3
FDS2070N7	150	Single	0.078	-	-	-	38	4.1	3
FDS2170N3	200	Single	0.128	-	-	-	26	3	3
FDS2170N7	200	Single	0.128	-	-	-	26	3	3
SO-8 FLMP P-Channel									
FDS7079ZN3	-30	Single	0.0075	0.0115	-	-	39	16	3.13
SO-8 N-Channel									
FDS6898A	20	Dual	-	0.014	0.018	-	16	9.4	2
FDS6898AZ	20	Dual	-	0.014	0.018	-	16	9.4	2
FDS6894A	20	Dual	-	0.017	0.02	0.03	17	8	2
FDS6894AZ	20	Dual	-	0.017	0.02	0.03	14	8	2
FDS6890A	20	Dual	-	0.018	0.022	-	23	7.5	2
FDS6892A	20	Dual	-	0.018	0.024	-	12	7.5	2
FDS6892AZ	20	Dual	-	0.018	0.024	-	12	7.5	2
FDS6812A	20	Dual	-	0.022	0.035	-	12	6.7	2
FDS9926A	20	Dual	-	0.03	0.043	-	7	6.5	2
FDS6574A	20	Single	-	0.006	0.007	0.009	75	16	2.5
FDS6572A	20	Single	-	0.006	0.008	-	57	16	2.5
FDS6570A	20	Single	-	0.0075	0.01	-	47	15	2.5
SI4466DY	20	Single	-	0.0075	0.01	-	47	15	2.5
NDS8426A	20	Single	-	0.0135	.016@2.7V	-	43	10.5	2.5
NDS8425	20	Single	-	0.022	.028@2.7V	-	11	7.4	2.5
FDS6982	30	Dual	0.015	0.02	-	-	18.5	8.6	2
	30		0.028	0.035			8.5	6.3	
FDS6990A	30	Dual	0.018	0.023	-	-	17	7.5	2
FDS8926A	30	Dual	-	0.03	0.038	-	19.8	5.5	2
FDS6912A	30	Dual	0.028	0.035	-	-	9	6	2
FDS8936A	30	Dual	0.028	0.04	-	-	19	6	2
FDS6912	30	Dual	0.028	0.042	-	-	7	6	2
FDS6930A	30	Dual	0.04	0.055	-	-	5	5.5	2
NDS9936	30	Dual	Use FDS6930A						
NDS9956A	30	Dual	0.08	0.11	-	-	9.5	3.7	2
FDS6961A	30	Dual	0.09	0.14	-	-	2.1	3.5	2
FDS6982S	30	Dual (MOSFET & SyncFET)	0.016	0.022	-	-	17.5	8.6	2
	30		0.028	0.035			8.5	6.3	
FDS6984S	30	Dual (MOSFET & SyncFET)	0.019	0.028	-	-	11	8.5	2
	30		0.04	0.055			5	5.5	
FDS6994S	30	Dual (MOSFET & SyncFET)	0.021	0.026	-	-	8	6.9	2
	30		0.015	0.0175			25	8.2	
FDS6986S	30	Dual (MOSFET & SyncFET)	0.029	0.038	-	-	6.5	6.5	2
	30		0.02	0.028			11	7.9	
FDS6900S	30	Dual (MOSFET & SyncFET)	0.03	0.037	-	-	8	6.9	2
	30		0.022	0.029			12	8.2	
FDS6990S	30	Dual SyncFET	0.022	0.03	-	-	11	7.5	2
FDS7788	30	Single	0.004	0.005	-	-	37	18	2.5
FDS7766	30	Single	0.005	0.006	-	-	43	17	2.5
FDS7764A	30	Single	-	0.0075	-	-	29	15	2.5
FDS7760A	30	Single	0.0055	0.008	-	-	37	15	2.5
FDS6688	30	Single	0.006	0.007	-	-	40	16	2.5

Products	BV _{DSS} Min (V)	Configuration	R _{DS(ON)} Max. (Ohms) @ V _{GS} =				Q _g (nC) Typ @ V _{GS} = 5V (Note pg. i)	Maximum Rating	
			10V	4.5V	2.5V	1.8V		I _D (A)	P _D (W)
SO-8 N-Channel (cont.)									
FDS6676	30	Single	0.007	0.008	-	-	45	14.5	2.5
FDS6688A	30	Single	Use FDS6676						
FDS6682	30	Single	0.0075	0.009	-	-	22	14	2.5
FDS6672A	30	Single	0.008	0.0095	-	-	33	12.5	2.5
FDS6670A	30	Single	0.008	0.01	-	-	35	13	2.5
FDS6644	30	Single	0.0085	0.0105	-	-	25	13	2.5
FDS7796	30	Single	0.009	0.012	-	-	16	13	2.5
FDS6680A	30	Single	0.0095	0.013	-	-	23	12.5	2.5
FDS6680	30	Single	0.01	0.015	-	-	19	11.5	2.5
ISL9N311ASK8T	30	Single	Use FDS6680						
FDS6694	30	Single	0.011	0.0135	-	-	13	12	2.5
FDS6294	30	Single	0.0113	0.0144	-	-	10	13	3
FDS6692	30	Single	0.012	0.0145	-	-	18	12	2.5
FDS6690A	30	Single	0.0125	0.017	-	-	17	11	2.5
ISL9N312ASK8T	30	Single	Use FDS6690A						
ISL9N316ASK8T	30	Single	Use FDS6690A						
FDS4410	30	Single	0.0135	0.02	-	-	13	10	2.5
FDS6690	30	Single	0.0135	0.02	-	-	13	10	2.5
FDS6614A	30	Single	0.018	0.025	-	-	12	9.3	2.5
FDS6678A	30	Single	0.02	0.024	-	-	13	7.5	2.5
FDS4488	30	Single	0.022	0.03	-	-	9.5	7.9	2.5
FDS6612A	30	Single	0.022	0.03	-	-	9	8.4	2.5
HUF76112SK8T	30	Single	Use FDS6612A						
HUF76121SK8	30	Single	Use FDS6612A						
ISL9N322ASK8T	30	Single	Use FDS6612A						
FDS9412	30	Single	0.022	0.036	-	-	9	7.9	2.5
FDS6630A	30	Single	0.038	0.053	-	-	5	6.5	2.5
FDS6676S	30	SyncFET	0.0052	0.006	-	-	43	14.5	2.5
FDS7766S	30	SyncFET	0.0055	0.0065	-	-	41	17	2.5
FDS7764S	30	SyncFET	0.0075	0.009	-	-	25	13.5	2.5
FDS6670S	30	SyncFET	0.009	0.0125	-	-	24	13.5	2.5
FDS6680S	30	SyncFET	0.011	0.017	-	-	17	11.5	2.5
FDS6690S	30	SyncFET	0.016	0.025	-	-	17	10	2.5
FDS4672A	40	Single	-	0.013	-	-	35	11	2.5
FDS4470	40	Single	0.009	-	-	-	45	12.5	2.5
FDS4770	40	Single	0.0105	-	-	-	47	13.2	2.5
FDS4780	40	Single	0.0105	-	-	-	30	10.8	2.5
FDS4480	40	Single	0.012	-	-	-	29	10.8	2.5
SSD2009A	50	Dual	0.13	0.2	-	-	19	3	2
SSD2007A	50	Dual	0.3	0.5@5V	-	-	11.5	2	2
HUFA76413DK8	60	Dual	0.049	0.056@5V	-	-	18	4.8	2.5
HUF76407DK8T	60	Dual	0.09	0.105	-	-	9.4	3.8	2.5
HUFA76407DK8T	60	Dual	0.09	0.105	-	-	9.4	3.8	2.5
FDS9945	60	Dual	0.1	0.2	-	-	8	3.5	2
SSD2025	60	Dual	0.1	0.2	-	-	15	3.3	2
FDS5670	60	Single	0.014	-	-	-	49	10	2.5
FDS5680	60	Single	0.02	-	-	-	30	8	2.5
FDS5690	60	Single	0.028	-	-	-	23	7	2.5
RF1K49154	60	Single	0.13	-	-	-	14	2	2
FDS3890	80	Dual	0.044	-	-	-	29	4.7	2
FDS3812	80	Dual	0.074	-	-	-	13	3.4	2
FDS3570	80	Single	0.019	-	-	-	54	9	2.5
FDS3580	80	Single	0.027	-	-	-	34	7.6	2.5

Products	BV _{DSS} Min (V)	Configuration	R _{DSD(ON)} Max. (Ohms) @ V _{GS} =				Q _g (nC) Typ @ V _{GS} = 5V (Note pg. i)	Maximum Rating	
			10V	4.5V	2.5V	1.8V		I _D (A)	P _D (W)
SO-8 N-Channel (cont.)									
HUF75531SK8	80	Single	0.03	-	-	-	37	6	2.5
HUFA75531SK8	80	Single	0.03	-	-	-	37	6	2.5
FDS3590	80	Single	0.037	-	-	-	23	6.5	2.5
FDS3512	80	Single	0.07	-	-	-	13	4	2.5
FDS3992	100	Dual	0.062	-	-	-	11	4.5	2.5
FDS3912	100	Dual	0.125	-	-	-	14	3	2
FDS3601	100	Dual	0.48	-	-	-	3.7	1.3	2
FDS3672	100	Single	0.022	-	-	-	28	7.5	2.5
FDS3670	100	Single	Use FDS3682						
FDS3680	100	Single	Use FDS3682						
FDS3682	100	Single	0.035	-	-	-	19	6	2.5
HUF75631SK8	100	Single	0.039	-	-	-	35	5.5	2.5
HUFA75631SK8	100	Single	0.039	-	-	-	35	5.5	2.5
FDS3690	100	Single	Use FDS3692						
FDS3692	100	Single	0.06	-	-	-	11	4.5	2.5
FDS3612	100	Single	0.12	-	-	-	14	3.4	2.5
FDS2572	150	Single	0.047	-	-	-	29	4.9	2.5
FDS2582	150	Single	0.066	-	-	-	11	4.5	2.5
FDS2570	150	Single	Use HUF75831SK8T						
HUF75831SK8T	150	Single	0.095	-	-	-	35	3	2.5
HUFA75831SK8T	150	Single	0.095	-	-	-	35	3	2.5
FDS2670	200	Single	0.13	-	-	-	27	3	2.5
FQS4901	400	Dual	4.2	-	-	-	5.8	0.45	2
FQS4903	500	Dual	6.2	-	-	-	6.3	0.37	2
SO-8 Complementary N- and P-Channel									
FDS8928A	30	Complementary	-	0.03	0.038	-	19.8	5.5	2
	-20			0.055	0.072		20	4	
NDH8321C	30	Complementary	Use FDS8928A						
FDS4501H	30	Complementary	0.018	0.046	0.063	-	17	9.3	2.5
	-20			0.023			13	5.6	
FDS8958A	30	Complementary	0.028	0.04	-	-	18	7	2
	-30		0.052	0.08			19	5	
NDH8521C	30	Complementary	Use FDS8958A						
SI4532DY	30	Complementary	0.065	0.095	-	-	3.7	3.9	2
	-30		0.085	0.19			5	3.5	
NDS9952A	30	Complementary	0.08	-	-	-	9.5	3.7	2
	-30		0.13				10	2.9	
FDS8333C	30	Complementary	0.08	0.13	-	-	4.7	4.1	2
	-30		0.13	0.2			4.1	3.4	
NDS9958	30	Complementary	Use FDS8333C						
FDS4559	60	Complementary	0.055	0.075	-	-	12.5	4.5	2
	-60		0.105	0.135			15	3.5	
FQS4900	60	Complementary	0.55	0.65@5V	-	-	1.6	1.3	2
	-300		15.5	16@5V			3.6	0.3	
SO-8 P-Channel									
NDS9948	-60	Dual	0.25	0.5	-	-	9	2.3	2
SSD2011A	-60	Dual	0.28	0.5	-	-	23	2	2
FDS4675	-40	Single	0.013	0.017	-	-	40	11	2.4
FDS4935	-30	Dual	0.023	0.035	-	-	15	7	2
FDS4935A	-30	Dual	0.023	0.035	-	-	15	7	2
FDS6975	-30	Dual	0.032	0.045	-	-	14.5	6	2
FDS8947A	-30	Dual	0.052	0.08	-	-	19	4	2
SI4953DY	-30	Dual	0.053	0.095	-	-	8	4.9	2
FDS6993	-30	Dual	0.055	0.017	0.024	0.03	-	4.3	2
	-12			0.085				6.8	

Products	BV _{DSS} Min (V)	Configuration	R _{DS(ON)} Max. (Ohms) @ V _{GS} =				Q _g (nC) Typ @ V _{GS} = 5V (Note pg. i)	Maximum Rating	
			10V	4.5V	2.5V	1.8V		I _D (A)	P _D (W)
SO-8 P-Channel (cont.)									
FDS4953	-30	Dual	0.055	0.095	-	-	6	5	2
FDS9953A	-30	Dual	0.13	0.2	-	-	2.5	2.9	2
NDS9953A	-30	Dual	Use FDS9953A						
FDS7779Z	-30	Single	0.0072	0.0115	-	-	70	16	3
FDS6679	-30	Single	0.009	0.013	-	-	71	13	2.5
FDS6679Z	-30	Single	0.009	0.013	-	-	67	13	2.5
FDS6675A	-30	Single	0.013	0.019	-	-	24	11	2.5
FDS6675	-30	Single	0.014	0.02	-	-	30	11	2.5
FDS4435A	-30	Single	0.017	0.025	-	-	21	9	2.5
FDS4435	-30	Single	0.02	0.035	-	-	17	8.8	2.5
FDS6685	-30	Single	0.02	0.035	-	-	19	8.8	2.5
FDS6609A	-30	Single	0.032	0.05	-	-	18	6	2.5
FDS9435A	-30	Single	0.05	0.08	-	-	10	5.3	2.5
NDS9435A	-30	Single	0.05	0.08	-	-	10	5.3	2.5
NDS9430	-30	Single	0.06	0.1	-	-	10	5.3	2.5
FDS9400A	-30	Single	0.13	0.2	-	-	2.4	3.4	2.5
NDS9400A	-30	Single	Use FDS9400A						
FDS6875	-20	Dual	-	0.03	0.04	-	23	6	2
FDS8934A	-20	Dual	-	0.055	0.072	-	20	4	2
FDS9933A	-20	Dual	-	0.075	0.105	-	8	3.8	2
NDS9933A	-20	Dual	-	0.14	0.2	-	6	2.8	2
RF1K49093	-20	Dual	Use NDS9933A						
FDS4465	-20	Single	-	0.0085	0.0105	0.014	86	13.5	2.5
FDS6575	-20	Single	-	0.013	0.017	-	50	10	2.5
FDS6576	-20	Single	-	0.014	0.02	-	43	11	2.5
FDS6375	-20	Single	-	0.024	0.032	-	23	8	2.5
FDS8433A	-20	Single	-	0.047	0.07	-	20	5	2.5
FDS9431A	-20	Single	-	0.13	0.18	-	6	3.5	2.5
TO-92 N-Channel									
BS270	60	Single	2	-	-	-	-	0.4	0.63
2N7000BU	60	Single	5	-	-	-	-	0.2	0.4
2N7000TA	60	Single	5	-	-	-	-	0.2	0.4
BS170	60	Single	5	-	-	-	-	0.5	0.83
SSN1N45B	450	Single	4.25	-	-	-	6.5	0.5	0.9
SOT-223 N-Channel									
NDT453N	30	Single	0.028	0.042	-	-	28	8	3
FDT439N	30	Single	-	0.045	0.058	-	10.7	6.3	3
NDT451AN	30	Single	0.035	0.05	-	-	19	7.2	3
FDT459N	30	Single	0.035	0.055	-	-	12	6.5	3
FDT457N	30	Single	0.06	0.09	-	-	4.2	5	3
HUF75309T3ST	55	Single	0.07	-	-	-	10.7	3	1.1
HUFA75309T3ST	55	Single	0.07	-	-	-	10.7	3	1.1
HUF75307T3ST	55	Single	0.09	-	-	-	8.3	2.6	1.1
NDT3055	60	Single	0.1	-	-	-	9	4	3
FQT13N06L	60	Single	0.11	0.14@5V	-	-	4.8	2.8	2.1
FQT13N06	60	Single	0.14	-	-	-	5.8	2.8	2.1
FDT3612	100	Single	0.12	-	-	-	14	3.7	3
IRFM120A	100	Single	0.2	-	-	-	16	2.3	2.4
FQT7N10	100	Single	0.35	-	-	-	5.8	1.7	2
IRLM120A	100	Single	-	0.22@5V	-	-	10.2	2.3	2.7
FQT7N10L	100	Single	0.35	0.38@5V	-	-	4.6	1.7	2
IRLM110A	100	Single	-	0.44@5V	-	-	5.5	1.5	2.2
IRFM110A	100	Single	0.4	-	-	-	8.5	1.5	2
IRFM220B	200	Single	0.8	-	-	-	12	1.1	2.4
FQT4N20L	200	Single	1.35	1.4@5V	-	-	4	0.85	2.2

Products	BV _{DSS} Min (V)	Configuration	R _{DS(ON)} Max. (Ohms) @ V _{GS} =				Q _g (nC) Typ @ V _{GS} = 5V (Note pg. i)	Maximum Rating	
			10V	4.5V	2.5V	1.8V		I _D (A)	P _D (W)
SOT-223 N-Channel (cont.)									
IRLM210A	200	Single	-	1.5@5V	-	-	6.1	0.77	1.8
FQT4N20	200	Single	1.4	-	-	-	5	0.85	2.2
IRFM210B	200	Single	1.5	-	-	-	7.2	0.77	2
IRFM224B	250	Single	1.1	-	-	-	13.5	0.92	2.5
FQT4N25	250	Single	1.75	-	-	-	4.3	0.83	2.5
IRFM214B	250	Single	2	-	-	-	8.1	0.64	2.1
SOT-223 P-Channel									
FQT2P25	-250	Single	4	-	-	-	6.5	0.55	2.5
SFM9214	-250	Single	4	-	-	-	9	0.45	1.6
FQT3P20	-200	Single	2.7	-	-	-	6	0.67	2.5
SFM9210	-200	Single	3	-	-	-	9	0.5	1.6
FQT5P10	-100	Single	1.05	-	-	-	6.3	1	2
SFM9110	-100	Single	1.2	-	-	-	9	1	2.5
NDT2955	-60	Single	0.3	0.5	-	-	11	2.5	3
SFM9014	-60	Single	0.5	-	-	-	9	1.8	2.8
NDT456P	-30	Single	0.03	0.045	-	-	47	7.5	3
NDT454P	-30	Single	0.05	0.09	-	-	29	5.9	3
NDT452AP	-30	Single	0.065	0.1	-	-	22	5	3
RFT2P03LT	-30	Single	Use NDT452AP						
FDT458P	-30	Single	0.13	0.2	-	-	2.5	3.4	3
FDT434P	-20	Single	-	0.05	0.07	-	13	6	3
SO-14 N-Channel									
FDQ7698S	30	Dual (MOSFET	0.012	0.016	-	-	12	12	2.4
	30	& SyncFET)	0.0075	0.009			43	15	
FDQ7244S	30	Dual (MOSFET	0.0145	0.016	-	-	33	11	2.4
	30	& SyncFET)	0.0095	0.0105			48	14	
TO-92L N-Channel									
IRFNL210B	200	Single	1.5	-	-	-	7.2	1	3.1
FQNL2N50B	500	Single	5.3	-	-	-	6	0.35	1.5
FQNL1N50B	500	Single	9	-	-	-	4	0.27	1.5
TO-251(IPAK) N-Channel									
FDU3706	20	Single	0.009	0.011	0.016	-	16	50	44
FDU6512A	20	Single	-	0.021	0.031	-	12	36	43
ISL9N306AD3	30	Single	0.006	0.0095	-	-	30	50	125
FDU6682	30	Single	0.0062	0.008	-	-	24	75	71
ISL9N308AD3	30	Single	0.008	-	-	-	24	50	100
FDU6696	30	Single	0.008	0.0107	-	-	17	50	52
FDU6644	30	Single	0.0085	0.0105	-	-	25	67	68
FDU6296	30	Single	0.0088	0.0113	-	-	22.5	50	52
FDU6680A	30	Single	0.0095	0.013	-	-	23	56	60
FDU7030BL	30	Single	0.0095	0.013	-	-	23	56	60
FDU6692	30	Single	0.012	0.0145	-	-	18	54	57
ISL9N312AD3	30	Single	0.012	0.02	-	-	13	50	75
ISL9N315AD3	30	Single	0.015	0.028	-	-	18	30	55
FDU6030BL	30	Single	0.016	0.022	-	-	22	42	50
FDU6612A	30	Single	0.02	0.028	-	-	9	30	36
HUFA75329D3	55	Single	0.026	-	-	-	32	20	128
HUFA75321D3	55	Single	0.036	-	-	-	21	20	93
HUFA75309D3	55	Single	0.07	-	-	-	11	19	55
HUFA75307D3	55	Single	0.09	-	-	-	9	15	45
HUFA76429D3	60	Single	0.023	0.027	-	-	38	20	110
HUF76423D3	60	Single	0.032	0.037	-	-	28	20	85
HUF76423D3	60	Single	0.032	0.037	-	-	28	20	85
HUF76419D3	60	Single	0.037	0.043	-	-	23	20	75
HUF76419D3	60	Single	0.037	0.043	-	-	23	20	75

Products	BV _{DSS} Min (V)	Configuration	R _{DS(ON)} Max. (Ohms) @ V _{GS} =				Q _g (nC) Typ @ V _{GS} = 5V (Note pg. i)	Maximum Rating	
			10V	4.5V	2.5V	1.8V		I _D (A)	P _D (W)
TO-251(IPAK) N-Channel (cont.)									
FQU30N06L	60	Single	0.039	0.047@5V	-	-	15	24	44
FQU30N06	60	Single	0.045	-	-	-	19	22.7	44
HUF76413D3	60	Single	0.049	0.056	-	-	17	20	60
HUFA76413D3	60	Single	0.049	0.056	-	-	17	20	60
FQU20N06L	60	Single	0.06	0.075@5V	-	-	9.5	17.2	38
FQU20N06	60	Single	0.063	-	-	-	11.5	16.8	38
HUF76409D3	60	Single	0.063	0.071	-	-	12	18	49
HUFA76409D3	60	Single	0.063	0.071	-	-	12	18	49
HUF76407D3	60	Single	0.092	0.107	-	-	9.4	12	38
HUFA76407D3	60	Single	0.092	0.107	-	-	9.4	12	38
FQU13N06L	60	Single	0.11	0.14@5V	-	-	4.8	11	28
FQU13N06	60	Single	0.14	-	-	-	5.8	10	28
FDU3580	80	Single	0.029	-	-	-	35	7.7	42
FQU24N08	80	Single	0.06	-	-	-	19	19.6	50
FQU17N08L	80	Single	0.1	0.115@5V	-	-	8.8	12.9	40
FQU9N08	80	Single	0.21	-	-	-	5.9	7.4	25
FQU9N08L	80	Single	0.21	0.23@5V	-	-	4.7	7.4	25
HUF76629D3	100	Single	0.052	0.054	-	-	38	20	110
HUFA76629D3	100	Single	0.052	0.054	-	-	38	20	110
HUF76619D3	100	Single	0.085	0.087	-	-	24	18	75
HUFA76619D3	100	Single	0.085	0.087	-	-	24	18	75
HUF75617D3	100	Single	0.09	-	-	-	18	16	64
HUFA75617D3	100	Single	0.09	-	-	-	18	16	64
FQU19N10	100	Single	0.1	-	-	-	19	15.6	50
FQU19N10L	100	Single	0.1	0.11@5V	-	-	14	15.6	50
IRLU130A	100	Single	-	0.12@5V	-	-	16.9	13	46
IRFU130A	100	Single	0.11	-	-	-	27	13	41
HUF76609D3	100	Single	0.16	0.165	-	-	13	10	49
HUFA76609D3	100	Single	0.16	0.165	-	-	13	10	49
FQU13N10	100	Single	0.18	-	-	-	12	10	40
FQU13N10L	100	Single	0.18	0.2@5V	-	-	8.7	10	40
IRLU120A	100	Single	-	0.22@5V	-	-	10.2	8.4	35
IRFU120A	100	Single	0.2	-	-	-	16	8.4	32
FQU7N10	100	Single	0.35	-	-	-	5.8	5.8	25
FQU7N10L	100	Single	0.35	0.38@5V	-	-	4.6	5.8	25
IRLU110A	100	Single	-	0.44@5V	-	-	5.5	4.7	22
IRFU110A	100	Single	0.4	-	-	-	8.5	4.7	20
FDU2572	150	Single	0.056	-	-	-	27	29	135
HUF75829D3	150	Single	0.11	-	-	-	31	18	110
HUF75823D3	150	Single	0.15	-	-	-	23	14	85
FQU14N15	150	Single	0.21	-	-	-	18	10	50
FQU9N15	150	Single	0.4	-	-	-	10	7	45
FQU5N15	150	Single	0.8	-	-	-	5.4	4.3	30
FQU18N20V2	200	Single	0.14	-	-	-	20	15	83
FQU12N20	200	Single	0.28	-	-	-	18	9	55
FQU12N20L	200	Single	0.28	0.32@5V	-	-	16	9	55
FQU10N20	200	Single	0.36	-	-	-	13.5	7.6	51
FQU10N20L	200	Single	0.36	0.38@5V	-	-	13	7.6	51
IRLU230A	200	Single	-	0.4@5V	-	-	18.6	7.5	48
IRFU230B	200	Single	0.4	-	-	-	22	7.5	50
FQU7N20	200	Single	0.69	-	-	-	8	5.3	45
FQU7N20L	200	Single	0.75	0.78@5V	-	-	6.8	5.5	45
IRFU220B	200	Single	0.8	-	-	-	12	4.6	40
FQU5N20	200	Single	1.2	-	-	-	6	3.8	37
FQU5N20L	200	Single	1.2	1.25@5V	-	-	4.8	3.8	37

Products	BV _{DSS} Min (V)	Configuration	R _{DS(ON)} Max. (Ohms) @ V _{GS} =				Q _g (nC) Typ @ V _{GS} = 5V (Note pg. i)	Maximum Rating	
			10V	4.5V	2.5V	1.8V		I _D (A)	P _D (W)
TO-251(IPAK) N-Channel (cont.)									
FQU4N20L	200	Single	1.35	1.4@5V	-	-	4	3.2	30
IRLU210A	200	Single	-	1.5@5V	-	-	6.1	2.7	21
FQU4N20	200	Single	1.4	-	-	-	5	3	30
IRFU210B	200	Single	1.5	-	-	-	7.2	2.7	26
FQU9N25	250	Single	0.42	-	-	-	15.5	7.4	55
IRFU234B	250	Single	0.45	-	-	-	29	6.6	49
FQU8N25	250	Single	0.55	-	-	-	12	6.2	50
FQU6N25	250	Single	1	-	-	-	6.6	4.4	45
IRFU224B	250	Single	1.1	-	-	-	13.5	3.8	42
FQU4N25	250	Single	1.75	-	-	-	4.3	3	37
IRFU214B	250	Single	2	-	-	-	8.1	2.2	25
FQU3N25	250	Single	2.2	-	-	-	4	2.4	30
FQU3N30	300	Single	2.2	-	-	-	5.5	2.4	30
FQU2N30	300	Single	3.7	-	-	-	3.7	1.7	25
IRFU330B	400	Single	1	-	-	-	25	4.5	48
FQU5N40	400	Single	1.6	-	-	-	10	3.4	45
IRFU320B	400	Single	1.75	-	-	-	14	3.1	41
FQU3N40	400	Single	3.4	-	-	-	6	2	30
IRFU310B	400	Single	3.4	-	-	-	7.7	1.7	26
FQU2N40	400	Single	5.8	-	-	-	4	1.4	25
IRFU430B	500	Single	1.5	-	-	-	25	3.5	48
FQU5N50	500	Single	1.8	-	-	-	13	3.5	50
IRFU420B	500	Single	2.6	-	-	-	14	2.3	41
FQU4N50	500	Single	2.7	-	-	-	10	2.6	45
FQU2N50B	500	Single	5.3	-	-	-	6	1.6	1.5
SSU1N50B	500	Single	5.5	-	-	-	8.3	1.3	26
FQU1N50	500	Single	9	-	-	-	4	1.1	25
FQU1N50B	500	Single	9	-	-	-	4	1.1	1.5
IRFU410B	500	Single	10	-	-	-	5.1	0.9	20
SSU4N60B	600	Single	2.5	-	-	-	22	2.8	49
FQU3N60	600	Single	3.6	-	-	-	10	2.4	50
FQU2N60	600	Single	4.7	-	-	-	9	2	45
SSU2N60B	600	Single	5	-	-	-	12.5	1.8	44
FQU1N60	600	Single	11.5	-	-	-	5	1	30
SSU1N60B	600	Single	12	-	-	-	5.9	0.9	28
FQU2N80	800	Single	6.3	-	-	-	12	1.8	50
FQU1N80	800	Single	20	-	-	-	5.5	1	45
FQU2N90	900	Single	7.2	-	-	-	12	1.7	50
TO-251(IPAK) P-Channel									
FQU3P50	-500	Single	4.9	-	-	-	18	2.1	50
FQU1P50	-500	Single	10.5	-	-	-	11	1.2	38
FQU4P40	-400	Single	3.1	-	-	-	18	2.7	50
FQU2P40	-400	Single	6.5	-	-	-	10	1.6	38
SFU9310	-400	Single	8	-	-	-	17	1.5	36
FQU6P25	-250	Single	1.1	-	-	-	21	4.7	55
FQU4P25	-250	Single	2.1	-	-	-	10	3.1	45
SFU9224	-250	Single	2.4	-	-	-	16	2.5	30
FQU2P25	-250	Single	4	-	-	-	6.5	2	37
SFU9214	-250	Single	4	-	-	-	9	1.5	19
SFU9230B	-200	Single	0.6	-	-	-	29	5.4	49
FQU7P20	-200	Single	0.69	-	-	-	19	5.7	55
FQU5P20	-200	Single	1.4	-	-	-	10	3.7	45
SFU9220	-200	Single	1.5	-	-	-	15	3.1	30
SFU9210	-200	Single	3	-	-	-	9	1.6	19
FQU12P10	-100	Single	0.29	-	-	-	21	9.4	50

Products	BV _{DSS} Min (V)	Configuration	R _{DS(ON)} Max. (Ohms) @ V _{GS} =				Q _g (nC) Typ @ V _{GS} = 5V (Note pg. i)	Maximum Rating	
			10V	4.5V	2.5V	1.8V		I _D (A)	P _D (W)
TO-251(IPAK) P-Channel (cont.)									
SFU9130	-100	Single	0.3	-	-	-	30	9.8	57
FQU8P10	-100	Single	0.53	-	-	-	12	6.6	44
SFU9120	-100	Single	0.6	-	-	-	16	4.9	32
FQU17P06	-60	Single	0.135	-	-	-	21	12	44
SFU9034	-60	Single	0.14	-	-	-	30	14	49
FQU11P06	-60	Single	0.185	-	-	-	13	9.4	38
SFU9024	-60	Single	0.28	-	-	-	15	7.8	32
SFU2955	-60	Single	0.3	-	-	-	15	7.6	32
FQU7P06	-60	Single	0.45	-	-	-	6.3	5.4	28
SFU9014	-60	Single	0.5	-	-	-	9	5.3	24
TO-252(DPAK) N-Channel									
FDD3706	20	Single	0.009	0.011	0.016	-	16	50	44
FDD6512A	20	Single	-	0.021	0.031	-	12	36	43
FDD6530A	20	Single	-	0.032	0.047	-	6.5	21	33
FDD6670AL	30	Single	0.005	0.006	-	-	37	84	83
FDD6688	30	Single	0.005	0.006	-	-	37	84	83
ISL9N306AD3ST	30	Single	0.006	0.0095	-	-	30	50	125
FDD6682	30	Single	0.0062	0.008	-	-	24	75	71
ISL9N307AD3ST	30	Single	0.007	0.0115	-	-	28	50	100
FDD6676	30	Single	0.0075	0.0085	-	-	45	78	83
FDD6672A	30	Single	0.008	0.0095	-	-	33	65	70
FDD6670A	30	Single	0.008	0.01	-	-	35	66	70
FDD6696	30	Single	0.008	0.0107	-	-	17	50	52
FDD6644	30	Single	0.0085	0.0105	-	-	25	67	68
FDD6296	30	Single	0.0088	0.0113	-	-	22.5	50	52
FDD6680A	30	Single	0.0095	0.013	-	-	23	56	60
FDD7030BL	30	Single	0.0095	0.013	-	-	23	56	60
ISL9N310AD3ST	30	Single	0.01	0.015	-	-	17	35	70
FDD6680	30	Single	0.011	0.017	-	-	17	55	60
FDD6692	30	Single	0.012	0.0145	-	-	18	54	57
ISL9N312AD3ST	30	Single	0.012	0.02	-	-	13	50	75
ISL9N316AD3ST	30	Single	Use ISL9N312AD3ST						
FDD6035AL	30	Single	0.0125	0.016	-	-	17	46	50
FDD6690A	30	Single	0.0125	0.016	-	-	17	46	50
FDD6030L	30	Single	0.0145	0.021	-	-	36	50	60
ISL9N315AD3ST	30	Single	0.015	0.028	-	-	18	30	55
FDD6030BL	30	Single	0.016	0.022	-	-	22	42	50
ISL9N318AD3ST	30	Single	0.018	0.03	-	-	8.6	30	55
FDD6612A	30	Single	0.02	0.028	-	-	9	30	36
RFD20N03SM	30	Single	Use FDD6612A						
ISL9N327AD3ST	30	Single	0.027	0.04	-	-	8.7	20	50
FDD6630A	30	Single	0.035	0.05	-	-	5	21	28
FDD6632	30	Single	0.09	0.104	-	-	2.6	9	15
FDD6676S	30	SyncFET	0.006	0.0071	-	-	41	78	70
FDD6644S	30	SyncFET	0.0085	0.01	-	-	25	66	57
FDD6670S	30	SyncFET	0.009	0.0125	-	-	17	64	70
FDD6680S	30	SyncFET	0.011	0.017	-	-	17	55	60
FDD6690S	30	SyncFET	0.0167	0.0245	-	-	17	40	50
RFD16N05LSM	50	Single	-	0.047	-	-	61	16	60
HUFA75329D3S	55	Single	0.026	-	-	-	32	20	128
HUFA75321D3S	55	Single	0.036	-	-	-	21	20	93
HUF75309D3S	55	Single	0.07	-	-	-	11	19	55
HUF75309D3S	55	Single	0.07	-	-	-	11	19	55
HUFA75307D3S	55	Single	0.09	-	-	-	9	15	45
FDD10AN06A0	60	Single	0.0105	-	-	-	28	50	135

Products	BV _{DSS} Min (V)	Configuration	R _{DS(ON)} Max. (Ohms) @ V _{GS} =				Q _g (nC) Typ @ V _{GS} = 5V (Note pg. i)	Maximum Rating	
			10V	4.5V	2.5V	1.8V		I _D (A)	P _D (W)
TO-252(DPAK) N-Channel (cont)									
FDD14AN06LA0	60	Single	0.011	0.014@5V	-	-	25	50	125
FDD13AN06A0	60	Single	0.013	-	-	-	22	50	115
FDD5670	60	Single	0.015	-	-	-	49	48	70
FDD5680	60	Single	0.021	-	-	-	33	38	60
HUF76429D3S	60	Single	0.023	0.027	-	-	38	20	110
HUFA76429D3S	60	Single	0.023	0.027	-	-	38	20	110
HUFA75429D3ST	60	Single	0.025	-	-	-	36	20	125
FDD5690	60	Single	0.027	-	-	-	23	30	50
HUF76423D3S	60	Single	0.032	0.037	-	-	28	20	85
HUFA76423D3S	60	Single	0.032	0.037	-	-	28	20	85
HUF76419D3S	60	Single	0.037	0.043	-	-	23	20	75
HUFA76419D3S	60	Single	0.037	0.043	-	-	23	20	75
RFD16N06LESM	60	Single	-	0.047	-	-	51	16	90
FQD30N06L	60	Single	0.039	0.047@5V	-	-	15	24	44
FQD30N06	60	Single	0.045	-	-	-	19	22.7	44
HUF76413D3S	60	Single	0.049	0.056	-	-	17	20	60
HUFA76413D3S	60	Single	0.049	0.056	-	-	17	20	60
FDD5612	60	Single	0.055	-	-	-	7.5	18	42
FQD20N06L	60	Single	0.06	0.075@5V	-	-	9.5	17.2	38
FQD20N06LE	60	Single	0.06	0.075@5V	-	-	9.5	17.2	38
FQD20N06	60	Single	0.063	-	-	-	11.5	16.8	38
HUF76409D3S	60	Single	0.063	0.071	-	-	12	18	49
HUFA76409D3S	60	Single	0.063	0.071	-	-	12	18	49
RFD12N06RLES	60	Single	0.063	0.075	-	-	12	18	49
HUF76407D3S	60	Single	0.092	0.107	-	-	9.4	12	38
HUFA76407D3S	60	Single	0.092	0.107	-	-	9.4	12	38
FQD13N06L	60	Single	0.11	0.14@5V	-	-	4.8	11	28
RFD4N06LSM	60	Single	-	0.6	-	-	6	4	30
FQD13N06	60	Single	0.14	-	-	-	7.5	10	28
FDD16AN08A0	75	Single	0.016	-	-	-	31	50	135
FDD3570	80	Single	0.019	-	-	-	54	10	69
FDD3580	80	Single	0.029	-	-	-	35	7.7	42
FQD24N08	80	Single	0.06	-	-	-	19	19.6	50
FQD17N08L	80	Single	0.1	0.115@5V	-	-	8.8	12.9	40
FQD17N08	80	Single	0.115	-	-	-	12	12.9	40
FQD9N08	80	Single	0.21	-	-	-	5.9	7.4	25
FQD9N08L	80	Single	0.21	0.23@5V	-	-	4.7	7.4	25
FDD3672	100	Single	0.028	-	-	-	24	44	135
FDD3670	100	Single	0.032	-	-	-	57	34	83
FDD3682	100	Single	0.036	-	-	-	18.5	32	95
FDD3680	100	Single	0.046	-	-	-	38	25	60
HUF76629D3S	100	Single	0.052	0.054	-	-	38	20	110
HUFA76629D3S	100	Single	0.052	0.054	-	-	38	20	110
FDD3690	100	Single	0.064	-	-	-	28	22	60
HUF76619D3S	100	Single	0.085	0.087	-	-	24	18	75
HUFA76619D3S	100	Single	0.085	0.087	-	-	24	18	75
HUF75617D3S	100	Single	0.09	-	-	-	18	16	64
HUFA75617D3S	100	Single	0.09	-	-	-	18	16	64
FQD19N10	100	Single	0.1	-	-	-	19	15.6	50
FQD19N10L	100	Single	0.1	0.11@5V	-	-	14	15.6	50
IRLR130A	100	Single	-	0.12@5V	-	-	16.9	13	46
IRFR130A	100	Single	0.11	-	-	-	27	13	41
HUF76609D3S	100	Single	0.16	0.165	-	-	13	10	49
HUFA76609D3S	100	Single	0.16	0.165	-	-	13	10	49
FQD13N10	100	Single	0.18	-	-	-	12	10	40

Products	BV _{DSS} Min (V)	Configuration	R _{DS(ON)} Max. (Ohms) @ V _{GS} =				Q _g (nC) Typ @ V _{GS} = 5V (Note pg. i)	Maximum Rating	
			10V	4.5V	2.5V	1.8V		I _D (A)	P _D (W)
TO-252(DPAK) N-Channel (cont.)									
FQD13N10L	100	Single	0.18	0.2@5V	-	-	8.7	10	40
IRLR120A	100	Single	-	0.22@5V	-	-	10.2	8.4	35
IRFR120A	100	Single	0.2	-	-	-	16	8.4	32
FQD7N10	100	Single	0.35	-	-	-	5.8	5.8	25
FQD7N10L	100	Single	0.35	0.38@5V	-	-	4.6	5.8	25
IRLR110A	100	Single	-	0.44@5V	-	-	5.5	4.7	22
IRFR110A	100	Single	0.4	-	-	-	8.5	4.7	20
FDD2572	150	Single	0.056	-	-	-	27	29	135
FDD2582	150	Single	0.077	-	-	-	19	21	310
FDD2570	150	Single	0.08	-	-	-	39	4.7	70
HUF75829D3S	150	Single	0.11	-	-	-	31	18	110
FDD120AN15A0	150	Single	0.12	-	-	-	11.2	14	65
HUF75823D3S	150	Single	0.15	-	-	-	23	14	85
FQD16N15	150	Single	0.16	-	-	-	23	11.8	55
FQD14N15	150	Single	0.21	-	-	-	18	10	50
FQD9N15	150	Single	0.4	-	-	-	10	7	45
FDD2512	150	Single	0.42	-	-	-	8	6.7	42
FQD6N15	150	Single	0.6	-	-	-	6.5	5.2	37
FQD5N15	150	Single	0.8	-	-	-	5.4	4.3	30
FDD2670	200	Single	0.13	-	-	-	27	3.6	70
FQD18N20V2	200	Single	0.14	-	-	-	20	15	83
HUF75925D3ST	200	Single	0.275	-	-	-	32	11	100
FQD12N20	200	Single	0.28	-	-	-	18	9	55
FQD12N20L	200	Single	0.28	0.32@5V	-	-	16	9	55
FQD10N20	200	Single	0.36	-	-	-	13.5	7.6	51
FQD10N20L	200	Single	0.36	0.38@5V	-	-	13	7.6	51
IRLR230A	200	Single	-	0.4@5V	-	-	18.6	7.5	48
FQD630	200	Single	0.4	-	-	-	19	7	46
IRFR230B	200	Single	0.4	-	-	-	22	7.5	50
FQD7N20	200	Single	0.69	-	-	-	8	5.3	45
FDD2612	200	Single	0.72	-	-	-	8	4.9	42
FQD7N20L	200	Single	0.75	0.78@5V	-	-	6.8	5.5	45
IRLR220A	200	Single	-	0.8@5V	-	-	10.3	4.6	33
IRFR220B	200	Single	0.8	-	-	-	12	4.6	40
FQD5N20	200	Single	1.2	-	-	-	6	3.8	37
FQD5N20L	200	Single	1.2	1.25@5V	-	-	4.8	3.8	37
FQD4N20L	200	Single	1.35	1.4@5V	-	-	4	3.2	30
IRLR210A	200	Single	-	1.5@5V	-	-	6.1	2.7	21
FQD4N20	200	Single	1.4	-	-	-	5	3	30
IRFR210B	200	Single	1.5	-	-	-	7.2	2.7	26
FQD9N25	250	Single	0.42	-	-	-	15.5	7.4	55
IRFR234B	250	Single	0.45	-	-	-	29	6.6	49
FQD8N25	250	Single	0.55	-	-	-	12	6.2	50
FQD6N25	250	Single	1	-	-	-	6.6	4.4	45
IRFR224B	250	Single	1.1	-	-	-	13.5	3.8	2.5
FQD4N25	250	Single	1.75	-	-	-	4.3	3	37
IRFR214B	250	Single	2	-	-	-	8.1	2.2	25
FQD3N25	250	Single	2.2	-	-	-	4	2.4	30
FQD7N30	300	Single	0.7	-	-	-	13	5.5	50
FQD5N30	300	Single	0.9	-	-	-	9.8	4.4	45
FQD3N30	300	Single	2.2	-	-	-	5.5	2.4	30
FQD2N30	300	Single	3.7	-	-	-	3.7	1.7	25
IRFR330B	400	Single	1	-	-	-	25	4.5	48
FQD6N40	400	Single	1.15	-	-	-	13	4.2	50
FQD5N40	400	Single	1.6	-	-	-	10	3.4	45

Products	BV _{DSS} Min (V)	Configuration	R _{DS(ON)} Max. (Ohms) @ V _{GS} =				Q _g (nC) Typ @ V _{GS} = 5V (Note pg. i)	Maximum Rating	
			10V	4.5V	2.5V	1.8V		I _D (A)	P _D (W)
TO-252(DPAK) N-Channel (cont.)									
IRFR320B	400	Single	1.75	-	-	-	14	3.1	41
FQD3N40	400	Single	3.4	-	-	-	6	2	30
IRFR310B	400	Single	3.4	-	-	-	7.7	1.7	26
FQD2N40	400	Single	5.8	-	-	-	4	1.4	25
IRFR430B	500	Single	1.5	-	-	-	25	3.5	48
FQD5N50	500	Single	1.8	-	-	-	13	3.5	50
IRFR420	500	Single	Use IRFR420B						
IRFR420B	500	Single	2.6	-	-	-	14	2.3	41
FQD4N50	500	Single	2.7	-	-	-	10	2.6	45
FQD2N50	500	Single	5.3	-	-	-	6	1.6	30
SSR1N50B	500	Single	5.5	-	-	-	8.3	1.3	26
FQD1N50	500	Single	9	-	-	-	4	1.1	25
SSR4N60B	600	Single	2.5	-	-	-	22	2.8	49
FQD3N60	600	Single	3.6	-	-	-	10	2.4	50
FQD2N60	600	Single	4.7	-	-	-	9	2	45
SSR2N60B	600	Single	5	-	-	-	12.5	1.8	44
FQD1N60	600	Single	11.5	-	-	-	5	1	30
SSR1N60B	600	Single	12	-	-	-	5.9	0.9	28
FQD2N80	800	Single	6.3	-	-	-	12	1.8	50
FQD1N80	800	Single	20	-	-	-	5.5	1	45
FQD2N90	900	Single	7.2	-	-	-	12	1.7	50
FQD2N100	1000	Single	10	-	-	-	12	1.7	50
TO-252(DPAK) P-Channel									
FQD3P50	-500	Single	4.9	-	-	-	18	2.1	50
FQD1P50	-500	Single	10.5	-	-	-	11	1.2	38
FQD4P40	-400	Single	3.1	-	-	-	18	2.7	50
FQD2P40	-400	Single	6.5	-	-	-	10	1.6	38
SFR9310	-400	Single	8	-	-	-	17	1.5	36
FQD6P25	-250	Single	1.1	-	-	-	21	4.7	55
FQD4P25	-250	Single	2.1	-	-	-	10	3.1	45
SFR9224	-250	Single	2.4	-	-	-	16	2.5	30
FQD2P25	-250	Single	4	-	-	-	6.5	2	37
SFR9214	-250	Single	4	-	-	-	9	1.5	19
SFR9230B	-200	Single	0.6	-	-	-	29	5.4	49
FQD7P20	-200	Single	0.69	-	-	-	19	5.7	55
FQD5P20	-200	Single	1.4	-	-	-	10	3.7	45
IRFR9220	-200	Single	Use SFR9220						
SFR9220	-200	Single	1.5	-	-	-	15	3.1	30
FQD3P20	-200	Single	2.7	-	-	-	6	2.4	37
SFR9210	-200	Single	3	-	-	-	9	1.6	19
FQD12P10	-100	Single	0.29	-	-	-	21	9.4	50
SFR9130	-100	Single	0.3	-	-	-	30	9.8	57
FQD8P10	-100	Single	0.53	-	-	-	12	6.6	44
SFR9120	-100	Single	0.6	-	-	-	16	4.9	32
FQD5P10	-100	Single	1.05	-	-	-	6.3	3.6	25
SFR9110	-100	Single	1.2	-	-	-	9	2.8	20
FDD5614P	-60	Single	0.1	0.13	-	-	15	15	42
FQD17P06	-60	Single	0.135	-	-	-	21	12	44
SFR9034	-60	Single	0.14	-	-	-	30	14	49
FQD11P06	-60	Single	0.185	-	-	-	13	9.4	38
SFR9024	-60	Single	0.28	-	-	-	15	7.8	32
SFR2955	-60	Single	0.3	-	-	-	15	7.6	32
FQD7P06	-60	Single	0.45	-	-	-	6.3	5.4	28
SFR9014	-60	Single	0.5	-	-	-	9	5.3	24

Products	BV _{DSS} Min (V)	Configuration	R _{DS(ON)} Max. (Ohms) @ V _{GS} =				Q _g (nC) Typ @ V _{GS} = 5V (Note pg. i)	Maximum Rating	
			10V	4.5V	2.5V	1.8V		I _D (A)	P _D (W)
DIP-8 Complementary N- and P-Channel									
FQG4902	250 -250	Complementary	2 2	-	-	-	6 12	0.54 0.54	1.4
FQG4904	400 -400	Complementary	3 3	-	-	-	7.6 20	0.46 0.46	1.6
TO-220 N-Channel									
ISL9N302AP3	30	Single	0.0025	0.0033	-	-	110	75	345
ISL9N303AP3	30	Single	0.0032	0.005	-	-	61	75	215
FDP8030L	30	Single	0.0035	0.0045	-	-	120	80	187
FDP7045L	30	Single	0.0045	0.006	-	-	50	100	125
ISL9N304AP3	30	Single	0.0045	0.0075	-	-	38	75	145
FDP6676	30	Single	0.006	0.0075	-	-	43	84	93
ISL9N306AP3	30	Single	0.006	0.0095	-	-	30	75	125
FDP6670AL	30	Single	0.0065	0.0085	-	-	24	80	68
FDP7030L	30	Single	0.007	0.01	-	-	35	100	125
ISL9N307AP3	30	Single	0.007	0.0115	-	-	28	75	100
FDP7042L	30	Single	0.0075	0.009	-	-	32	50	83
FDP7030BL	30	Single	0.009	0.012	-	-	23	60	65
ISL9N310AP3	30	Single	0.01	0.015	-	-	17	62	70
RFP70N03	30	Single	Use ISL9N310AP3						
FDP6035L	30	Single	0.011	0.019	-	-	34	58	75
ISL9N312AP3	30	Single	0.012	0.02	-	-	13	58	75
ISL9N316AP3	30	Single	Use ISL9N312AP3						
FDP6035AL	30	Single	0.0125	0.017	-	-	17	48	58
FDP6030L	30	Single	0.0135	0.02	-	-	34	52	75
FQP45N03L	30	Single	0.014	0.02	-	-	13	21	55
FDB6603AL	30	Single	Use FDP6030BL						
FDP6030BL	30	Single	0.018	0.024	-	-	12	40	60
HUF76009P3	30	Single	Use FDP6030BL						
HUF76107P3	30	Single	0.052	0.085	-	-	4.7	20	35
FDP6676S	30	SyncFET	0.0065	0.008	-	-	40	76	70
FDP6670S	30	SyncFET	0.0085	0.0105	-	-	23	62	62.5
FDP6644S	30	SyncFET	0.01	0.012	-	-	27	55	60
FDP6690S	30	SyncFET	0.0155	0.023	-	-	11	42	48
HUF75229P3	50	Single	0.022	-	-	-	35	44	90
BUZ11	50	Single	0.04	-	-	-	-	30	75
HUF75345P3	55	Single	0.007	-	-	-	125	75	325
HUFA75345P3	55	Single	0.007	-	-	-	125	75	325
HUF75344P3	55	Single	0.008	-	-	-	90	75	285
HUFA75344P3	55	Single	0.008	-	-	-	90	75	285
HUF75343P3	55	Single	0.009	-	-	-	92	75	270
HUFA75343P3	55	Single	0.009	-	-	-	92	75	270
HUF75339P3	55	Single	0.012	-	-	-	60	75	200
HUFA75339P3	55	Single	0.012	-	-	-	60	75	200
HUF75337P3	55	Single	0.014	-	-	-	51	75	175
HUFA75337P3	55	Single	0.014	-	-	-	51	75	175
HUF75333P3	55	Single	0.016	-	-	-	40	66	150
HUFA75333P3	55	Single	0.016	-	-	-	40	66	150
HUF75332P3	55	Single	0.019	-	-	-	40	60	145
HUFA75332P3	55	Single	0.019	-	-	-	40	60	145
HUFA75329P3	55	Single	0.024	-	-	-	35	49	128
HUF75329P3	55	Single	0.026	-	-	-	35	49	128
HUF75321P3	55	Single	0.034	-	-	-	21	35	93
HUFA75321P3	55	Single	0.034	-	-	-	21	35	93
HUF75309P3	55	Single	0.07	-	-	-	11	19	55
HUFA75309P3	55	Single	0.07	-	-	-	11	19	55

Products	BV _{DSS} Min (V)	Configuration	R _{DS(ON)} Max. (Ohms) @ V _{GS} =				Q _g (nC) Typ @ V _{GS} = 5V (Note pg. i)	Maximum Rating	
			10V	4.5V	2.5V	1.8V		I _D (A)	P _D (W)
TO-220 N-Channel (cont.)									
HUFA75307P3	55	Single	0.09	-	-	-	9	15	45
FDP038AN06A0	60	Single	0.0038	-	-	-	95	80	310
FDP050AN06A0	60	Single	0.005	-	-	-	61	80	245
HUF76445P3	60	Single	0.0065	0.0075	-	-	124	75	310
HUFA76445P3	60	Single	0.0065	0.0075	-	-	124	75	310
FDP070AN06A0	60	Single	0.007	-	-	-	51	15	175
HUF76443P3	60	Single	0.008	0.0095	-	-	107	75	260
HUFA76443P3	60	Single	0.008	0.0095	-	-	107	75	260
FDP5645	60	Single	0.0095	-	-	-	76	80	125
FQP85N06	60	Single	0.01	-	-	-	86	85	160
FDP10AN06A0	60	Single	0.0105	-	-	-	28	75	135
FDP14AN06LA0	60	Single	0.011	0.014@5V	-	-	24	61	125
HUF76439P3	60	Single	0.012	0.014	-	-	70	75	180
HUFA76439P3	60	Single	0.012	0.014	-	-	70	75	180
FDP13AN06A0	60	Single	0.013	-	-	-	22	64	115
HUFA76437P3	60	Single	0.014	0.017	-	-	59	71	155
FQP65N06	60	Single	0.016	-	-	-	48	65	150
HUF76432P3	60	Single	0.017	0.019	-	-	44	59	130
HUFA76432P3	60	Single	0.017	0.019	-	-	44	59	130
FDP20AN06A0	60	Single	0.02	-	-	-	15	45	90
FDP5680	60	Single	0.02	-	-	-	33	40	65
FQP55N06	60	Single	0.02	-	-	-	35	55	133
FQP50N06L	60	Single	0.021	0.025@5V	-	-	24.5	52	121
FQP50N06	60	Single	0.022	-	-	-	31	50	120
HUF76429P3	60	Single	0.022	0.025	-	-	38	47	110
HUFA76429P3	60	Single	0.022	0.025	-	-	38	47	110
FDP5690	60	Single	0.027	-	-	-	23	32	58
HUF76423P3	60	Single	0.03	0.035	-	-	28	35	85
HUFA76423P3	60	Single	0.03	0.035	-	-	28	35	85
HUF76419P3	60	Single	0.035	0.04	-	-	22	29	75
HUFA76419P3	60	Single	0.035	0.04	-	-	22	29	75
FQP30N06L	60	Single	0.035	0.045@5V	-	-	15	32	79
FQP30N06	60	Single	0.04	-	-	-	19	30	79
HUFA76413P3	60	Single	0.049	0.056	-	-	17	23	60
FQP20N06L	60	Single	0.055	0.07@5V	-	-	9.5	21	53
FQP20N06	60	Single	0.06	-	-	-	11.5	20	53
HUF76409P3	60	Single	0.062	0.07	-	-	12	18	49
HUFA76409P3	60	Single	0.062	0.07	-	-	12	18	49
HUF76407P3	60	Single	0.092	0.107	-	-	9.4	13	38
HUFA76407P3	60	Single	0.092	0.107	-	-	9.4	13	38
FQP13N06L	60	Single	0.11	0.14@5V	-	-	4.8	13.6	45
FQP13N06	60	Single	0.135	-	-	-	5.8	13	45
FDP047AN08A0	75	Single	0.0047	-	-	-	92	80	310
FDP060AN08A0	75	Single	0.006	-	-	-	99	80	285
FDP16AN08A0	75	Single	0.016	-	-	-	28	58	135
HUF75545P3	80	Single	0.01	-	-	-	105	75	270
HUFA75545P3	80	Single	0.01	-	-	-	105	75	270
HUF75542P3	80	Single	0.014	-	-	-	80	75	230
HUFA75542P3	80	Single	0.014	-	-	-	80	75	230
FQP90N08	80	Single	0.016	-	-	-	84	71	160
FQP70N08	80	Single	0.017	-	-	-	75	70	155
FQP58N08	80	Single	0.024	-	-	-	50	57	146
FQP44N08	80	Single	0.034	-	-	-	38	44	127
FQP24N08	80	Single	0.06	-	-	-	19	24	75
FQP17N08L	80	Single	0.1	0.115@5V	-	-	8.8	16.5	65

Products	BV _{DSS} Min (V)	Configuration	R _{DS(ON)} Max. (Ohms) @ V _{GS} =				Q _g (nC) Typ @ V _{GS} = 5V (Note pg. i)	Maximum Rating	
			10V	4.5V	2.5V	1.8V		I _D (A)	P _D (W)
TO-220 N-Channel (cont.)									
FQP17N08	80	Single	0.115	-	-	-	12	16.5	65
FQP9N08	80	Single	0.21	-	-	-	5.9	9.3	40
FQP9N08L	80	Single	0.21	0.23@5V	-	-	4.7	9.3	40
FDP3632	100	Single	0.009	-	-	-	84	80	310
HUF75645P3	100	Single	0.014	-	-	-	106	75	310
HUFA75645P3	100	Single	0.014	-	-	-	106	75	310
HUF76645P3	100	Single	0.014	0.015	-	-	127	75	310
HUFA76645P3	100	Single	0.014	0.015	-	-	127	75	310
FDP3652	100	Single	0.016	-	-	-	44	61	150
FQP70N10	100	Single	0.025	-	-	-	85	57	160
HUF75639P3	100	Single	0.025	-	-	-	57	56	200
HUFA75639P3	100	Single	0.025	-	-	-	57	56	200
FQP55N10	100	Single	0.026	-	-	-	75	55	155
HUF76639P3	100	Single	0.026	0.027	-	-	71	51	180
HUFA76639P3	100	Single	0.026	0.027	-	-	71	51	180
HUF75637P3	100	Single	0.03	-	-	-	48	44	155
HUFA75637P3	100	Single	0.03	-	-	-	48	44	155
HUF76633P3	100	Single	0.035	0.036	-	-	56	39	145
HUFA76633P3	100	Single	0.035	0.036	-	-	56	39	145
FDP3682	100	Single	0.036	-	-	-	18.5	32	95
FQP44N10	100	Single	0.039	-	-	-	48	43.5	146
HUF75631P3	100	Single	0.04	-	-	-	35	33	120
HUFA75631P3	100	Single	0.04	-	-	-	35	33	120
IRF550A	100	Single	0.04	-	-	-	75	40	167
FQP33N10	100	Single	0.052	-	-	-	38	33	127
IRF540A	100	Single	0.052	-	-	-	60	28	107
FQP33N10L	100	Single	0.052	0.055@5V	-	-	30	33	127
IRL540A	100	Single	-	0.058@5V	-	-	38.4	28	121
HUF75623P3	100	Single	0.064	-	-	-	23	22	85
HUFA75623P3	100	Single	0.064	-	-	-	23	22	85
FQP19N10	100	Single	0.1	-	-	-	19	19	75
FQP19N10L	100	Single	0.1	0.11@5V	-	-	14	19	75
IRL530A	100	Single	-	0.12@5V	-	-	16.9	14	62
IRF530A	100	Single	0.11	-	-	-	27	14	55
FQP13N10	100	Single	0.18	-	-	-	12	12.8	65
FQP13N10L	100	Single	0.18	0.2@5V	-	-	8.7	12.8	65
IRL520A	100	Single	-	0.22@5V	-	-	10.2	9.2	49
IRF520A	100	Single	0.2	-	-	-	16	9.2	45
FQP7N10	100	Single	0.35	-	-	-	5.8	7.3	40
FQP7N10L	100	Single	0.35	0.38@5V	-	-	4.6	7.3	40
IRL510A	100	Single	-	0.44@5V	-	-	5.5	5.6	37
IRF510A	100	Single	0.4	-	-	-	8.5	5.6	33
FDP3672	105	Single	0.033	-	-	-	28	41	135
FDP2532	150	Single	0.016	-	-	-	86	79	310
FDP2552	150	Single	0.036	-	-	-	41	37	150
FDP42AN15A0	150	Single	0.042	-	-	-	30	35	150
FQP46N15	150	Single	0.042	-	-	-	85	45.6	210
HUF75842P3	150	Single	0.042	-	-	-	77	43	230
HUFA75842P3	150	Single	0.042	-	-	-	77	43	230
FDP2572	150	Single	0.056	-	-	-	27	29	135
FDP2570	150	Single	0.08	-	-	-	40	22	93
FQP28N15	150	Single	0.09	-	-	-	40	28	168
FDP120AN15A0	150	Single	0.12	-	-	-	11.2	14	65
FQP16N15	150	Single	0.16	-	-	-	23	16.4	108
FQP14N15	150	Single	0.21	-	-	-	18	14.4	104

Products	BV _{DSS} Min (V)	Configuration	R _{D(S(ON))} Max. (Ohms) @ V _{GS} =				Q _g (nC) Typ @ V _{GS} = 5V (Note pg. i)	Maximum Rating	
			10V	4.5V	2.5V	1.8V		I _D (A)	P _D (W)
TO-220 N-Channel (cont.)									
FQP9N15	150	Single	0.4	-	-	-	10	9	75
FQP6N15	150	Single	0.6	-	-	-	6.5	6.4	63
SSP45N20B	200	Single	0.065	-	-	-	133	35	176
FQP34N20	200	Single	0.075	-	-	-	60	31	180
FQP34N20L	200	Single	0.075	0.08@5V	-	-	55	31	180
IRL640A	200	Single	-	0.18@5V	-	-	40	18	110
IRF650B	200	Single	0.085	-	-	-	95	28	156
HUF75939P3	200	Single	0.125	-	-	-	64	22	180
FDP2670	200	Single	0.13	-	-	-	27	19	93
FQP18N20V2	200	Single	0.14	-	-	-	20	18	-
FQP19N20L	200	Single	0.14	0.15@5V	-	-	27	21	140
FQP19N20	200	Single	0.15	-	-	-	31	19.4	140
IRF640B	200	Single	0.18	-	-	-	45	18	139
HUF75925P3	200	Single	0.275	-	-	-	32	11	100
FQP12N20L	200	Single	0.28	0.32@5V	-	-	16	11.6	90
FQP10N20	200	Single	0.36	-	-	-	13.5	10	87
FQP10N20C	200	Single	0.36	-	-	-	20	9.5	72
FQP10N20L	200	Single	0.36	0.38@5V	-	-	13	10	87
IRL630A	200	Single	-	0.4@5V	-	-	18.6	9	69
FQP630	200	Single	0.4	-	-	-	19	9	78
IRF630B	200	Single	0.4	-	-	-	22	9	72
FQP7N20	200	Single	0.69	-	-	-	8	6.6	63
FQP7N20L	200	Single	0.75	0.78@5V	-	-	6.8	6.5	63
IRL620A	200	Single	-	0.8@5V	-	-	10.3	5	39
IRF620B	200	Single	0.8	-	-	-	12	5	47
FQP5N20	200	Single	1.2	-	-	-	6	4.5	52
FQP5N20L	200	Single	1.2	1.25@5V	-	-	4.8	4.5	52
FQP4N20L	200	Single	1.35	1.4@5V	-	-	4	3.8	45
IRL610A	200	Single	-	1.5@5V	-	-	6.1	3.3	33
FQP4N20	200	Single	1.4	-	-	-	5	3.6	45
IRF610B	200	Single	1.5	-	-	-	7.2	3.3	38
FQP27N25	250	Single	0.11	-	-	-	50	25.5	180
IRF654B	250	Single	0.14	-	-	-	95	15	156
FQP16N25	250	Single	0.23	-	-	-	27	16	142
IRF644B	250	Single	0.28	-	-	-	47	14	139
FQP9N25	250	Single	0.42	-	-	-	15.5	9.4	90
IRF634B	250	Single	0.45	-	-	-	29	8.1	74
FQP6N25	250	Single	1	-	-	-	6.6	5.5	63
IRF624B	250	Single	1.1	-	-	-	13.5	4.1	49
FQP4N25	250	Single	1.75	-	-	-	4.3	3.6	52
IRF614B	250	Single	2	-	-	-	8.1	2.8	40
FQP3N25	250	Single	2.2	-	-	-	4	2.8	45
FQP22N30	300	Single	0.16	-	-	-	47	21	170
FQP14N30	300	Single	0.29	-	-	-	30	9.1	147
FQP9N30	300	Single	0.45	-	-	-	17	9	98
FQP5N30	300	Single	0.9	-	-	-	9.8	5.4	70
FQP3N30	300	Single	2.2	-	-	-	5.5	3.2	55
FQP2N30	300	Single	3.7	-	-	-	3.7	1.3	16
FDP20N40	400	Single	0.216	-	-	-	35	20	273
FQP17N40	400	Single	0.27	-	-	-	45	16	170
FDP13N40	400	Single	0.37	-	-	-	18.3	13	250
FQP11N40	400	Single	0.48	-	-	-	27	11.4	147
IRF740B	400	Single	0.54	-	-	-	41	10	134
FQP7N40	400	Single	0.8	-	-	-	16.5	7	98
FQP6N40C	400	Single	1	-	-	-	16	6	73

Products	BV _{DSS} Min (V)	Configuration	R _{DS(ON)} Max. (Ohms) @ V _{GS} =				Q _g (nC) Typ @ V _{GS} = 5V (Note pg. i)	Maximum Rating	
			10V	4.5V	2.5V	1.8V		I _D (A)	P _D (W)
TO-220 N-Channel (cont.)									
IRF730B	400	Single	1	-	-	-	25	5.5	73
FQP5N40	400	Single	1.6	-	-	-	10	4.5	70
IRF720B	400	Single	1.75	-	-	-	14	3.3	46
FQP3N40	400	Single	3.4	-	-	-	6	2.5	55
IRF710B	400	Single	3.4	-	-	-	7.7	2	36
IRFF320	400	Single	Use IRF710B						
FQP2N40	400	Single	5.8	-	-	-	4	1.8	40
FQP6N45	450	Single	1.1	-	-	-	16	6.2	98
FQP18N50V2	500	Single	0.265	-	-	-	42	18	208
FDP15N50	500	Single	0.38	-	-	-	33	15	250
FQP13N50	500	Single	0.43	-	-	-	45	12.5	170
FQP13N50C	500	Single	0.48	-	-	-	43	13	195
FDP11N50	500	Single	0.725	-	-	-	17	11	250
FQP9N50	500	Single	0.73	-	-	-	28	9	147
FQP9N50C	500	Single	0.8	-	-	-	28	9	135
IRF840A	500	Single	Use IRF840B						
IRF840B	500	Single	0.85	-	-	-	41	8	134
FQP6N50	500	Single	1.3	-	-	-	17	5.5	98
FQP5N50C	500	Single	1.4	-	-	-	18	5	73
IRF830B	500	Single	1.5	-	-	-	27	4.5	73
IRF820B	500	Single	2.6	-	-	-	14	2.5	49
FQP4N50	500	Single	2.7	-	-	-	10	3.4	70
FQP2N50	500	Single	5.3	-	-	-	6	2.1	55
SSP1N50B	500	Single	5.5	-	-	-	8.3	1.5	36
FQP1N50	500	Single	9	-	-	-	4	1.4	40
FDP14N60	600	Single	0.49	-	-	-	36	14	300
FQP12N60C	600	Single	0.65	-	-	-	48	12	225
FQP12N60	600	Single	0.7	-	-	-	42	10.5	180
FQP10N60C	600	Single	0.73	-	-	-	44	9.5	156
SSP10N60B	600	Single	0.8	-	-	-	54	9	156
FQP7N60	600	Single	1	-	-	-	29	7.4	142
FQP8N60C	600	Single	1.2	-	-	-	28	7.5	147
SSP7N60B	600	Single	1.2	-	-	-	38	7	147
FQP6N60	600	Single	1.5	-	-	-	20	6.2	130
FQP4N60	600	Single	2.2	-	-	-	15	4.4	106
SSP4N60B	600	Single	2.5	-	-	-	22	4	100
FQP3N60	600	Single	3.6	-	-	-	10	3	75
FQP2N60	600	Single	4.7	-	-	-	9	2.4	64
SSP2N60B	600	Single	5	-	-	-	12.5	2	54
FQP1N60	600	Single	11.5	-	-	-	5	1.2	40
SSP1N60B	600	Single	12	-	-	-	5.9	1	34
FQP6N70	700	Single	1.5	-	-	-	30	6.2	142
SSP6N70A	700	Single	1.8	-	-	-	51	6	130
FQP8N80C	800	Single	1.55	-	-	-	35	8	178
FQP7N80C	800	Single	1.9	-	-	-	27	6.6	167
FQP6N80	800	Single	1.95	-	-	-	31	5.8	158
FQP6N80C	800	Single	2.5	-	-	-	21	5.5	158
FQP5N80	800	Single	2.6	-	-	-	25	4.8	140
FQP4N80	800	Single	3.6	-	-	-	19	3.9	130
FQP3N80C	800	Single	4.8	-	-	-	13	3	107
FQP3N80	800	Single	5	-	-	-	15	3	107
SSP3N80A	800	Single	Use FQP3N80						
FQP2N80	800	Single	6.3	-	-	-	12	2.4	85
FQP5N90	900	Single	2.3	-	-	-	31	5.4	158
FQP6N90C	900	Single	2.3	-	-	-	30	6	167

Products	BV _{DSS} Min (V)	Configuration	R _{Ds(ON)} Max. (Ohms) @ V _{GS} =				Q _g (nC) Typ @ V _{GS} = 5V (Note pg. i)	Maximum Rating	
			10V	4.5V	2.5V	1.8V		I _D (A)	P _D (W)
TO-220 N-Channel (cont.)									
FQP4N90	900	Single	3.1	-	-	-	24	4.2	140
FQP4N90C	900	Single	4.2	-	-	-	17	4	140
FQP3N90	900	Single	4.25	-	-	-	20	3.6	130
SSP4N90A	900	Single	Use FQP3N90						
FQP2NA90	900	Single	5.8	-	-	-	15	2.8	107
FQP2N90	900	Single	7.2	-	-	-	12	2.2	85
TO-220 P-Channel									
FQP3P50	-500	Single	4.9	-	-	-	18	2.7	85
FQP1P50	-500	Single	10.5	-	-	-	11	1.5	63
FQP4P40	-400	Single	3.1	-	-	-	18	3.5	85
FQP2P40	-400	Single	6.5	-	-	-	10	2	63
FQP9P25	-250	Single	0.62	-	-	-	29	9.4	120
SFP9644	-250	Single	0.8	-	-	-	45	8.6	123
FQP6P25	-250	Single	1.1	-	-	-	21	6	90
SFP9634	-250	Single	1.3	-	-	-	29	5	70
FQP4P25	-250	Single	2.1	-	-	-	10	4	75
FQP2P25	-250	Single	4	-	-	-	6.5	2.3	52
SFP9614	-250	Single	4	-	-	-	9	1.6	20
FQP12P20	-200	Single	0.47	-	-	-	31	11.5	120
SFP9640	-200	Single	0.5	-	-	-	46	11	123
FQP7P20	-200	Single	0.69	-	-	-	19	7.3	90
SFP9630	-200	Single	0.8	-	-	-	29	6.5	70
FQP5P20	-200	Single	1.4	-	-	-	10	4.8	75
SFP9620	-200	Single	1.5	-	-	-	15	3.5	38
FQP3P20	-200	Single	2.7	-	-	-	6	2.8	52
SFP9610	-200	Single	3	-	-	-	9	1.8	20
SFP9640L	-200	Single	-	0.5@5V	-	-	46	11	98
FQP22P10	-100	Single	0.125	-	-	-	40	22	125
FQP17P10	-100	Single	0.19	-	-	-	30	16.5	100
SFP9540	-100	Single	0.2	-	-	-	43	17	132
FQP12P10	-100	Single	0.29	-	-	-	21	11.5	75
SFP9530	-100	Single	0.3	-	-	-	30	10.5	66
FQP8P10	-100	Single	0.53	-	-	-	12	8	65
SFP9520	-100	Single	0.6	-	-	-	16	6	49
FQP5P10	-100	Single	1.05	-	-	-	6.3	4.5	40
SFP9510	-100	Single	1.2	-	-	-	9	3.6	32
FQP47P06	-60	Single	0.026	-	-	-	84	47	160
FQP27P06	-60	Single	0.07	-	-	-	33	27	120
FQP17P06	-60	Single	0.12	-	-	-	21	17	79
SFP9Z34	-60	Single	0.14	-	-	-	30	18	82
FQP11P06	-60	Single	0.175	-	-	-	13	11.4	53
SFP9Z24	-60	Single	0.28	-	-	-	15	9.7	49
SFP2955	-60	Single	0.3	-	-	-	15	9.4	49
FQP7P06	-60	Single	0.41	-	-	-	6.3	6.7	45
SFP9Z14	-60	Single	0.5	-	-	-	9	6.7	38
NDP6020P	-20	Single	-	0.05	0.075 0.07@2.7V	-	25	24	60
FDP4020P	-20	Single	-	0.08	0.11	-	9.5	16	37.5
TO-262(I²PAK) N-Channel									
ISL9N303AS3	30	Single	0.0032	0.005	-	-	61	75	215
HUF75345S3	55	Single	0.007	-	-	-	125	75	325
HUF75333S3	55	Single	0.016	-	-	-	40	66	150
FDI038AN06A0	60	Single	0.0038	-	-	-	95	80	310
FQI50N06L	60	Single	0.021	0.025@5V	-	-	24.5	52	121
FQI50N06	60	Single	0.022	-	-	-	31	50	120

Products	BV _{DSS} Min (V)	Configuration	R _{DS(ON)} Max. (Ohms) @ V _{GS} =				Q _g (nC) Typ @ V _{GS} = 5V (Note pg. i)	Maximum Rating	
			10V	4.5V	2.5V	1.8V		I _D (A)	P _D (W)
TO-262(I²PAK) N-Channel (cont.)									
FQI30N06L	60	Single	0.035	0.045@5V	-	-	15	32	79
RF1S25N06	60	Single	0.047	-	-	-	35	25	72
FQI13N06L	60	Single	0.11	0.14@5V	-	-	4.8	13.6	45
FQI13N06	60	Single	0.135	-	-	-	5.8	13	45
HUF7554S3	80	Single	0.01	-	-	-	105	75	270
FQI90N08	80	Single	0.016	-	-	-	84	71	160
FQI70N08	80	Single	0.017	-	-	-	75	70	155
FQI44N08	80	Single	0.034	-	-	-	38	44	127
FQI17N08L	80	Single	0.1	0.115@5V	-	-	8.8	16.5	65
FQI17N08	80	Single	0.115	-	-	-	12	16.5	65
FQI9N08	80	Single	0.21	-	-	-	5.9	9.3	40
FQI9N08L	80	Single	0.21	0.23@5V	-	-	4.7	9.3	40
FDI3632	100	Single	0.009	-	-	-	84	80	310
FDI3652	100	Single	0.016	-	-	-	44	61	150
FQI70N10	100	Single	0.025	-	-	-	85	57	160
HUF75639S3	100	Single	0.025	-	-	-	57	56	200
FQI44N10	100	Single	0.039	-	-	-	48	43.5	146
IRFI550A	100	Single	0.04	-	-	-	75	40	167
FQI33N10	100	Single	0.052	-	-	-	38	33	127
IRFI540A	100	Single	0.052	-	-	-	60	28	107
FQI33N10L	100	Single	0.052	0.055@5V	-	-	30	33	127
IRLI540A	100	Single	-	0.058@5V	-	-	38.4	28	121
FQI19N10	100	Single	0.1	-	-	-	19	19	75
FQI19N10L	100	Single	0.1	0.11@5V	-	-	14	19	75
IRLI530A	100	Single	-	0.12@5V	-	-	16.9	14	62
IRFI530A	100	Single	0.11	-	-	-	27	14	55
FQI13N10	100	Single	0.18	-	-	-	12	12.8	65
FQI13N10L	100	Single	0.18	0.2@5V	-	-	8.7	12.8	65
IRLI520A	100	Single	-	0.22@5V	-	-	10.2	9.2	49
IRFI520A	100	Single	0.2	-	-	-	16	9.2	45
FQI7N10	100	Single	0.35	-	-	-	5.8	7.3	40
FQI7N10L	100	Single	0.35	0.38@5V	-	-	4.6	7.3	40
IRLI510A	100	Single	-	0.44@5V	-	-	5.5	5.6	37
IRFI510A	100	Single	0.4	-	-	-	8.5	5.6	33
FDI2532	150	Single	0.016	-	-	-	86	79	310
FQI28N15	150	Single	0.09	-	-	-	40	28	168
FQI16N15	150	Single	0.16	-	-	-	23	16.4	108
FQI9N15	150	Single	0.4	-	-	-	10	9	75
FQI6N15	150	Single	0.6	-	-	-	6.5	6.4	63
FQI5N15	150	Single	0.8	-	-	-	5.4	5.4	54
FQI34N20	200	Single	0.075	-	-	-	60	31	180
IRFI650B	200	Single	0.085	-	-	-	95	28	156
FQI19N20L	200	Single	0.14	0.15@5V	-	-	27	21	140
FQI19N20	200	Single	0.15	-	-	-	31	19.4	140
IRFI640B	200	Single	0.18	-	-	-	45	18	139
FQI12N20L	200	Single	0.28	0.32@5V	-	-	16	11.6	90
FQI10N20L	200	Single	0.36	0.38@5V	-	-	13	10	87
IRLI630A	200	Single	-	0.4@5V	-	-	18.6	9	69
IRFI630B	200	Single	0.4	-	-	-	22	9	72
FQI7N20	200	Single	0.69	-	-	-	8	6.6	63
FQI7N20L	200	Single	0.75	0.78@5V	-	-	6.8	6.5	63
IRLI620A	200	Single	-	0.8@5V	-	-	10.3	5	39
IRFI620B	200	Single	0.8	-	-	-	12	5	47
FQI5N20	200	Single	1.2	-	-	-	6	4.5	52
FQI5N20L	200	Single	1.2	1.25@5V	-	-	4.8	4.5	52

Products	BV _{DSS} Min (V)	Configuration	R _{DSD(ON)} Max. (Ohms) @ V _{GS} =				Q _g (nC) Typ @ V _{GS} = 5V (Note pg. i)	Maximum Rating	
			10V	4.5V	2.5V	1.8V		I _D (A)	P _D (W)
TO-262(I²PAK) N-Channel (cont.)									
FQI4N20L	200	Single	1.35	1.4@5V	-	-	4	3.8	45
IRLI610A	200	Single	-	1.5@5V	-	-	6.1	3.3	33
FQI4N20	200	Single	1.4	-	-	-	5	3.6	45
IRFI610B	200	Single	1.5	-	-	-	7.2	3.3	38
FQI27N25	250	Single	0.11	-	-	-	50	25.5	180
IRFI654B	250	Single	0.14	-	-	-	95	15	156
IRFI644B	250	Single	0.28	-	-	-	47	14	139
IRFI634B	250	Single	0.45	-	-	-	29	8.1	74
IRFI624B	250	Single	1.1	-	-	-	13.5	4.1	49
FQI4N25	250	Single	1.75	-	-	-	4.3	3.6	52
IRFI614B	250	Single	2	-	-	-	8.1	2.8	40
FQI3N25	250	Single	2.2	-	-	-	4	2.8	45
FQI5N30	300	Single	0.9	-	-	-	9.8	5.4	70
FQI3N30	300	Single	2.2	-	-	-	5.5	3.2	55
FQI2N30	300	Single	3.7	-	-	-	3.7	2.1	40
FQI11N40	400	Single	0.48	-	-	-	27	11.4	147
IRFI740B	400	Single	0.54	-	-	-	41	10	134
FQI7N40	400	Single	0.8	-	-	-	16.5	7	98
FQI6N40	400	Single	1.15	-	-	-	13	5.5	85
FQI5N40	400	Single	1.6	-	-	-	10	4.5	70
FQI3N40	400	Single	3.4	-	-	-	6	2.5	55
FQI6N45	450	Single	1.1	-	-	-	16	6.2	98
FQI9N50	500	Single	0.73	-	-	-	28	9	147
IRFI840B	500	Single	0.85	-	-	-	41	8	134
IRFI830B	500	Single	1.5	-	-	-	27	4.5	73
FQI5N50	500	Single	1.8	-	-	-	13	4.5	85
SSI1N50B	500	Single	5.5	-	-	-	8.3	1.5	36
FQI12N60	600	Single	0.7	-	-	-	42	10.5	180
SSI10N60B	600	Single	0.8	-	-	-	54	9	156
FQI7N60	600	Single	1	-	-	-	29	7.4	142
SSI7N60B	600	Single	1.2	-	-	-	38	7	147
FQI4N60	600	Single	2.2	-	-	-	15	4.4	106
SSI4N60B	600	Single	2.5	-	-	-	22	4	100
SSI2N60B	600	Single	5	-	-	-	12.5	2	54
SSI1N60B	600	Single	12	-	-	-	5.9	1	34
FQI6N70	700	Single	1.5	-	-	-	30	6.2	142
FQI7N80	800	Single	1.5	-	-	-	40	6.6	167
FQI5N80	800	Single	2.6	-	-	-	25	4.8	140
FQI4N80	800	Single	3.6	-	-	-	19	3.9	130
FQI3N80	800	Single	5	-	-	-	15	3	107
FQI2N80	800	Single	6.3	-	-	-	12	2.4	85
FQI6N90	900	Single	1.9	-	-	-	40	5.8	167
FQI5N90	900	Single	2.3	-	-	-	31	5.4	158
FQI4N90	900	Single	3.1	-	-	-	24	4.2	140
FQI3N90	900	Single	4.25	-	-	-	20	3.6	130
FQI2NA90	900	Single	5.8	-	-	-	15	2.8	107
FQI2N90	900	Single	7.2	-	-	-	12	2.2	85
TO-262(I²PAK) P-Channel									
FQI3P50	-500	Single	4.9	-	-	-	18	2.7	85
FQI1P50	-500	Single	10.5	-	-	-	11	1.5	63
FQI4P40	-400	Single	3.1	-	-	-	18	3.5	85
FQI2P40	-400	Single	6.5	-	-	-	10	2	63
FQI9P25	-250	Single	0.62	-	-	-	29	9.4	120
SFI9644	-250	Single	0.8	-	-	-	45	8.6	123
FQI6P25	-250	Single	1.1	-	-	-	21	6	90

Products	BV _{DSS} Min (V)	Configuration	R _{DS(ON)} Max. (Ohms) @ V _{GS} =				Q _g (nC) Typ @ V _{GS} = 5V (Note pg. i)	Maximum Rating	
			10V	4.5V	2.5V	1.8V		I _D (A)	P _D (W)
TO-262(I²PAK) P-Channel (cont.)									
SFI9634	-250	Single	1.3	-	-	-	29	5	70
SFI9624	-250	Single	2.4	-	-	-	16	2.7	38
FQI2P25	-250	Single	4	-	-	-	6.5	2.3	52
SFI9614	-250	Single	4	-	-	-	9	1.6	20
FQI12P20	-200	Single	0.47	-	-	-	31	11.5	120
SFI9640	-200	Single	0.5	-	-	-	46	11	123
FQI7P20	-200	Single	0.69	-	-	-	19	7.3	90
SFI9630	-200	Single	0.8	-	-	-	29	6.5	70
FQI5P20	-200	Single	1.4	-	-	-	10	4.8	75
FQI3P20	-200	Single	2.7	-	-	-	6	2.8	52
SFI9610	-200	Single	3	-	-	-	9	1.8	20
FQI17P10	-100	Single	0.19	-	-	-	30	16.5	100
SFI9540	-100	Single	0.2	-	-	-	43	17	132
FQI12P10	-100	Single	0.29	-	-	-	21	11.5	75
SFI9530	-100	Single	0.3	-	-	-	30	10.5	66
FQI8P10	-100	Single	0.53	-	-	-	12	8	65
SFI9520	-100	Single	0.6	-	-	-	16	6	49
FQI5P10	-100	Single	1.05	-	-	-	6.3	4.5	40
SFI9510	-100	Single	1.2	-	-	-	9	3.6	32
FQI47P06	-60	Single	0.026	-	-	-	84	47	160
FQI27P06	-60	Single	0.07	-	-	-	33	27	120
FQI17P06	-60	Single	0.12	-	-	-	21	17	79
SFI9Z34	-60	Single	0.14	-	-	-	30	18	82
FQI11P06	-60	Single	0.175	-	-	-	13	11.4	53
SFI9Z24	-60	Single	0.28	-	-	-	15	9.7	49
SFI2955	-60	Single	0.3	-	-	-	15	9.4	49
FQI7P06	-60	Single	0.41	-	-	-	6.3	7	45
SFI9Z14	-60	Single	0.5	-	-	-	9	6.7	38
TO-263(D²PAK) N-Channel									
ISL9N302AS3ST	30	Single	0.0023	0.0033	-	-	110	75	345
ISL9N303AS3ST	30	Single	0.0026	0.004	-	-	61	75	215
FDB8030L	30	Single	0.0035	0.0045	-	-	120	80	187
FDB7045L	30	Single	0.0045	0.006	-	-	50	100	125
ISL9N304AS3ST	30	Single	0.0045	0.0075	-	-	38	75	145
FDB6676	30	Single	0.006	0.0075	-	-	43	84	93
ISL9N306AS3ST	30	Single	0.006	0.0095	-	-	30	75	125
FQB95N03L	30	Single	0.0064	0.01	-	-	24	40	80
FDB6670AL	30	Single	0.0065	0.0085	-	-	24	80	68
FDB7030L	30	Single	0.007	0.01	-	-	35	100	125
ISL9N307AS3ST	30	Single	0.007	0.0115	-	-	28	75	100
FDB7042L	30	Single	0.0075	0.009	-	-	32	50	83
FDB6644	30	Single	0.0085	0.0105	-	-	27	50	83
FDB7030BL	30	Single	0.009	0.012	-	-	23	60	65
ISL9N310AS3ST	30	Single	0.01	0.015	-	-	17	62	70
FQB60N03L	30	Single	0.01	0.017	-	-	13	55	60
FDB6035L	30	Single	0.011	0.019	-	-	34	58	75
ISL9N312AS3ST	30	Single	0.012	0.02	-	-	13	58	75
ISL9N316AS3ST	30	Single	Use ISL9N312AS3ST						
FDB6035AL	30	Single	0.0125	0.017	-	-	17	48	58
FDB6030L	30	Single	0.0135	0.02	-	-	34	52	75
HUF76129S3S	30	Single	0.016	0.023	-	-	19	56	105
FDB6030BL	30	Single	0.018	0.024	-	-	12	40	60
FDB4030L	30	Single	Use FDB603AL						
FDB603AL	30	Single	0.022	0.036	-	-	19	33	50
FDB6676S	30	SyncFET	0.0065	0.008	-	-	40	76	70

Products	BV _{DSS} Min (V)	Configuration	R _{Ds(ON)} Max. (Ohms) @ V _{GS} =				Q _g (nC) Typ @ V _{GS} = 5V (Note pg. i)	Maximum Rating	
			10V	4.5V	2.5V	1.8V		I _D (A)	P _D (W)
TO-263(D²PAK) N-Channel (cont.)									
FDB6670S	30	SyncFET	0.0085	0.0105	-	-	23	62	62.5
FDB6644S	30	SyncFET	0.01	0.012	-	-	27	55	60
FDB7030BLS	30	SyncFET	0.0105	0.0165	-	-	15	56	65
FDB6690S	30	SyncFET	0.0155	0.023	-	-	11	42	48
HUF75345S3S	55	Single	0.007	-	-	-	125	75	325
HUFA75345S3S	55	Single	0.007	-	-	-	125	75	325
HUF75344S3S	55	Single	0.008	-	-	-	90	75	285
HUFA75344S3S	55	Single	0.008	-	-	-	90	75	285
HUFA75343S3S	55	Single	0.009	-	-	-	92	75	270
HUFA75339S3S	55	Single	0.012	-	-	-	60	75	200
HUF75337S3S	55	Single	0.014	-	-	-	51	75	175
HUFA75337S3S	55	Single	0.014	-	-	-	51	75	175
HUF75333S3S	55	Single	0.016	-	-	-	40	66	150
HUF75332S3S	55	Single	0.019	-	-	-	40	60	145
HUFA75332S3S	55	Single	0.019	-	-	-	40	60	145
HUFA75329S3S	55	Single	0.024	-	-	-	35	49	128
HUF75321S3S	55	Single	0.034	-	-	-	21	35	93
HUFA75321S3S	55	Single	0.034	-	-	-	21	35	93
FDB035AN06A0	60	Single	0.0035	-	-	-	95	80	310
FDB050AN06A0	60	Single	0.005	-	-	-	61	80	245
HUF76445S3S	60	Single	0.0065	0.0075	-	-	124	75	310
HUFA76445S3S	60	Single	0.0065	0.0075	-	-	124	75	310
FDB070AN06A0	60	Single	0.007	-	-	-	51	15	175
HUF76443S3S	60	Single	0.008	0.0095	-	-	107	75	260
HUFA76443S3S	60	Single	0.008	0.0095	-	-	107	75	260
FDB5645	60	Single	0.0095	-	-	-	76	80	125
FQB85N06	60	Single	0.01	-	-	-	86	85	160
FDB10AN06A0	60	Single	0.0105	-	-	-	28	75	135
FDB14AN06LA0	60	Single	0.011	0.014@5V	-	-	24	61	125
HUF76439S3S	60	Single	0.012	0.014	-	-	70	75	180
HUFA76439S3S	60	Single	0.012	0.014	-	-	70	75	180
FDB13AN06A0	60	Single	0.013	-	-	-	22	64	115
HUF76437S3S	60	Single	0.014	0.017	-	-	59	71	155
HUFA76437S3S	60	Single	0.014	0.017	-	-	59	71	155
FQB65N06	60	Single	0.016	-	-	-	48	65	150
HUFA75433S3ST	60	Single	0.016	-	-	-	50	64	150
HUF76432S3S	60	Single	0.017	0.019	-	-	44	59	130
HUFA76432S3S	60	Single	0.017	0.019	-	-	44	59	130
FDB20AN06A0	60	Single	0.02	-	-	-	15	45	90
FDB5680	60	Single	0.02	-	-	-	33	40	65
FQB55N06	60	Single	0.02	-	-	-	35	55	133
FQB50N06L	60	Single	0.021	0.025@5V	-	-	24.5	52	121
FQB50N06	60	Single	0.022	-	-	-	31	50	120
RF1S50N06SM	60	Single	0.022	-	-	-	67	50	131
HUF76429S3S	60	Single	0.022	0.025	-	-	38	47	110
HUFA76429S3S	60	Single	0.022	0.025	-	-	38	47	110
FDB5690	60	Single	0.027	-	-	-	23	32	58
HUF76423S3S	60	Single	0.03	0.035	-	-	28	35	85
HUFA76423S3S	60	Single	0.03	0.035	-	-	28	35	85
HUF76419S3S	60	Single	0.035	0.04	-	-	22	29	75
HUFA76419S3S	60	Single	0.035	0.04	-	-	22	29	75
FQB30N06L	60	Single	0.035	0.045@5V	-	-	15	32	79
FQB30N06	60	Single	0.04	-	-	-	19	30	79
FQB20N06L	60	Single	0.055	0.07@5V	-	-	9.5	21	53
FQB20N06	60	Single	0.06	-	-	-	11.5	20	53

Products	BV _{DSS} Min (V)	Configuration	R _{DS(ON)} Max. (Ohms) @ V _{GS} =				Q _g (nC) Typ @ V _{GS} = 5V (Note pg. i)	Maximum Rating	
			10V	4.5V	2.5V	1.8V		I _D (A)	P _D (W)
TO-263(D²PAK) N-Channel (cont.)									
FQB13N06L	60	Single	0.11	0.14@5V	-	-	4.8	13.6	45
FQB13N06	60	Single	0.135	-	-	-	5.8	13	45
FDB045AN08A0	75	Single	0.0045	-	-	-	92	80	310
FDB060AN08A0	75	Single	0.006	-	-	-	99	80	285
FDB16AN08A0	75	Single	0.016	-	-	-	28	58	135
HUF75545S3S	80	Single	0.01	-	-	-	105	75	270
HUFA75545S3S	80	Single	0.01	-	-	-	105	75	270
HUF75542S3S	80	Single	0.014	-	-	-	80	75	230
HUFA75542S3S	80	Single	0.014	-	-	-	80	75	230
FQB90N08	80	Single	0.016	-	-	-	84	71	160
FQB70N08	80	Single	0.017	-	-	-	75	70	155
FQB44N08	80	Single	0.034	-	-	-	38	44	127
FQB24N08	80	Single	0.06	-	-	-	19	24	75
FQB17N08L	80	Single	0.1	0.115@5V	-	-	8.8	16.5	65
FQB17N08	80	Single	0.115	-	-	-	12	16.5	65
FQB9N08	80	Single	0.21	-	-	-	5.9	9.3	40
FQB9N08L	80	Single	0.21	0.23@5V	-	-	4.7	9.3	40
FDB3632	100	Single	0.009	-	-	-	84	80	310
HUF75645S3S	100	Single	0.014	-	-	-	106	75	310
HUFA75645S3S	100	Single	0.014	-	-	-	106	75	310
HUF76645S3S	100	Single	0.014	0.015	-	-	127	75	310
HUFA76645S3S	100	Single	0.014	0.015	-	-	127	75	310
FDB3652	100	Single	0.016	-	-	-	44	61	150
FQB70N10	100	Single	0.025	-	-	-	85	57	160
HUF75639S3S	100	Single	0.025	-	-	-	57	56	200
HUFA75639S3S	100	Single	0.025	-	-	-	57	56	200
FQB55N10	100	Single	0.026	-	-	-	75	55	155
HUF76639S3S	100	Single	0.026	0.027	-	-	71	51	180
HUFA76639S3S	100	Single	0.026	0.027	-	-	71	51	180
HUF75637S3S	100	Single	0.03	-	-	-	48	44	155
HUFA75637S3S	100	Single	0.03	-	-	-	48	44	155
HUF76633S3S	100	Single	0.035	0.036	-	-	56	39	145
HUFA76633S3S	100	Single	0.035	0.036	-	-	56	39	145
FDB3682	100	Single	0.036	-	-	-	18.5	32	95
FQB44N10	100	Single	0.039	-	-	-	48	43.5	146
HUF75631S3S	100	Single	0.04	-	-	-	35	33	120
HUFA75631S3S	100	Single	0.04	-	-	-	35	33	120
IRFW550A	100	Single	0.04	-	-	-	75	40	167
RF1S40N10SM	100	Single	0.04	-	-	-	115	40	160
FQB33N10	100	Single	0.052	-	-	-	38	33	127
IRFW540A	100	Single	0.052	-	-	-	60	28	107
FQB33N10L	100	Single	0.052	0.055@5V	-	-	30	33	127
IRLW540A	100	Single	-	0.058@5V	-	-	38.4	28	121
HUF75623S3S	100	Single	0.064	-	-	-	23	22	85
HUFA75623S3S	100	Single	0.064	-	-	-	23	22	85
FQB19N10	100	Single	0.1	-	-	-	19	19	75
FQB19N10L	100	Single	0.1	0.11@5V	-	-	14	19	75
IRLW530A	100	Single	-	0.12@5V	-	-	16.9	14	62
IRFW530A	100	Single	0.11	-	-	-	27	14	55
FQB13N10	100	Single	0.18	-	-	-	12	12.8	65
FQB13N10L	100	Single	0.18	0.2@5V	-	-	8.7	12.8	65
IRLW520A	100	Single	-	0.22@5V	-	-	10.2	9.2	49
IRFW520A	100	Single	0.2	-	-	-	16	9.2	45
FQB7N10	100	Single	0.35	-	-	-	5.8	7.3	40
FQB7N10L	100	Single	0.35	0.38@5V	-	-	4.6	7.3	40

Products	BV _{DSS} Min (V)	Configuration	R _{DS(ON)} Max. (Ohms) @ V _{GS} =				Q _g (nC) Typ @ V _{GS} = 5V (Note pg. i)	Maximum Rating	
			10V	4.5V	2.5V	1.8V		I _D (A)	P _D (W)
TO-263(D²PAK) N-Channel (cont.)									
IRLW510A	100	Single	-	0.44@5V	-	-	5.5	5.6	37
IRFW510A	100	Single	0.4	-	-	-	8.5	5.6	33
FDB2532	150	Single	0.016	-	-	-	86	79	310
FDB2552	150	Single	0.036	-	-	-	41	37	150
FDB42AN15A0	150	Single	0.042	-	-	-	30	35	150
FQB46N15	150	Single	0.042	-	-	-	85	45.6	210
HUFA75842S3S	150	Single	0.042	-	-	-	77	43	230
FDB2572	150	Single	0.056	-	-	-	27	29	135
FDB2570	150	Single	0.08	-	-	-	40	22	93
FQB16N15	150	Single	0.16	-	-	-	23	16.4	108
FQB14N15	150	Single	0.21	-	-	-	18	14.4	104
FQB9N15	150	Single	0.4	-	-	-	10	9	75
FQB6N15	150	Single	0.6	-	-	-	6.5	6.4	63
FQB5N15	150	Single	0.8	-	-	-	5.4	5.4	54
FQB34N20	200	Single	0.075	-	-	-	60	31	180
IRFW650B	200	Single	0.085	-	-	-	95	28	156
FDB2670	200	Single	0.13	-	-	-	27	19	93
FQB19N20L	200	Single	0.14	0.15@5V	-	-	27	21	140
IRLW640A	200	Single	-	0.18@5V	-	-	40	18	110
FQB19N20	200	Single	0.15	-	-	-	31	19.4	140
IRFW640B	200	Single	0.18	-	-	-	45	18	139
FQB12N20	200	Single	0.28	-	-	-	18	11.6	90
FQB12N20L	200	Single	0.28	0.32@5V	-	-	16	11.6	90
FQB10N20	200	Single	0.36	-	-	-	13.5	10	87
FQB10N20L	200	Single	0.36	0.38@5V	-	-	13	10	87
IRLW630A	200	Single	-	0.4@5V	-	-	18.6	9	69
FQB630	200	Single	0.4	-	-	-	19	9	78
IRFW630B	200	Single	0.4	-	-	-	22	9	72
FQB7N20	200	Single	0.69	-	-	-	8	6.6	63
FQB7N20L	200	Single	0.75	0.78@5V	-	-	6.8	6.5	63
IRLW620A	200	Single	-	0.8@5V	-	-	10.3	5	39
IRFW620B	200	Single	0.8	-	-	-	12	5	47
FQB5N20	200	Single	1.2	-	-	-	6	4.5	52
FQB5N20L	200	Single	1.2	1.25@5V	-	-	4.8	4.5	52
FQB4N20L	200	Single	1.35	1.4@5V	-	-	4	3.8	45
IRLW610A	200	Single	-	1.5@5V	-	-	6.1	3.3	33
FQB4N20	200	Single	1.4	-	-	-	5	3.6	45
IRFW610B	200	Single	1.5	-	-	-	7.2	3.3	38
FQB27N25	250	Single	0.11	-	-	-	50	25.5	180
IRFW654B	250	Single	0.14	-	-	-	95	15	156
FQB16N25	250	Single	0.23	-	-	-	27	16	142
IRFW644B	250	Single	0.28	-	-	-	47	14	139
FQB9N25	250	Single	0.42	-	-	-	15.5	9.4	90
IRFW634B	250	Single	0.45	-	-	-	29	8.1	74
FQB8N25	250	Single	0.55	-	-	-	12	8	87
FQB6N25	250	Single	1	-	-	-	6.6	5.5	63
IRFW624B	250	Single	1.1	-	-	-	13.5	4.1	49
FQB4N25	250	Single	1.75	-	-	-	4.3	3.6	52
IRFW614B	250	Single	2	-	-	-	8.1	2.8	40
FQB3N25	250	Single	2.2	-	-	-	4	2.8	45
FQB14N30	300	Single	0.29	-	-	-	30	9.1	147
FQB7N30	300	Single	0.7	-	-	-	13	7	85
FQB5N30	300	Single	0.9	-	-	-	9.8	5.4	70
FQB3N30	300	Single	2.2	-	-	-	5.5	3.2	55
FQB2N30	300	Single	3.7	-	-	-	3.7	2.1	40

Products	BV _{DSS} Min (V)	Configuration	R _{DS(ON)} Max. (Ohms) @ V _{GS} =				Q _g (nC) Typ @ V _{GS} = 5V (Note pg. i)	Maximum Rating	
			10V	4.5V	2.5V	1.8V		I _D (A)	P _D (W)
TO-263(D²PAK) N-Channel (cont.)									
FQB11N40	400	Single	0.48	-	-	-	27	11.4	147
IRFW740B	400	Single	0.54	-	-	-	41	10	134
FQB7N40	400	Single	0.8	-	-	-	16.5	7	98
IRFW730B	400	Single	1	-	-	-	25	5.5	73
FQB5N40	400	Single	1.6	-	-	-	10	4.5	70
IRFW720B	400	Single	1.75	-	-	-	14	3.3	46
FQB3N40	400	Single	3.4	-	-	-	6	2.5	55
IRFW710B	400	Single	3.4	-	-	-	7.7	2	36
FQB6N45	450	Single	1.1	-	-	-	16	6.2	98
FQB12N50	500	Single	0.43	-	-	-	45	12.5	170
FQB9N50	500	Single	0.73	-	-	-	28	9	147
IRFW840B	500	Single	0.85	-	-	-	41	8	134
FQB6N50	500	Single	1.3	-	-	-	17	5.5	98
IRFW830B	500	Single	1.5	-	-	-	27	4.5	73
FQB5N50	500	Single	1.8	-	-	-	13	4.5	85
IRFW820B	500	Single	2.6	-	-	-	14	2.5	49
FQB4N50	500	Single	2.7	-	-	-	10	3.4	70
FQB2N50	500	Single	5.3	-	-	-	6	2.1	55
SSW1N50B	500	Single	5.5	-	-	-	8.3	1.5	36
FQB12N60	600	Single	0.7	-	-	-	42	10.5	180
SSW10N60B	600	Single	0.8	-	-	-	54	9	156
FQB7N60	600	Single	1	-	-	-	29	7.4	142
SSW7N60B	600	Single	1.2	-	-	-	38	7	147
FQB6N60	600	Single	1.5	-	-	-	20	6.2	130
FQB5N60	600	Single	2	-	-	-	16	5	120
FQB4N60	600	Single	2.2	-	-	-	15	4.4	106
SSW4N60B	600	Single	2.5	-	-	-	22	4	100
FQB2N60	600	Single	4.7	-	-	-	9	2.4	64
SSW2N60B	600	Single	5	-	-	-	12.5	2	54
FQB1N60	600	Single	11.5	-	-	-	5	1.2	40
SSW1N60B	600	Single	12	-	-	-	5.9	1	34
FQB6N70	700	Single	1.5	-	-	-	30	6.2	142
FQB6N80	800	Single	1.95	-	-	-	31	5.8	158
FQB5N80	800	Single	2.6	-	-	-	25	4.8	140
SSW4N80AS	800	Single	Use FQB5N80						
FQB4N80	800	Single	3.6	-	-	-	19	3.9	130
FQB3N80	800	Single	5	-	-	-	15	3	107
SSW3N80A	800	Single	Use FQB3N80						
FQB2N80	800	Single	6.3	-	-	-	12	2.4	85
FQB5N90	900	Single	2.3	-	-	-	31	5.4	158
FQB4N90	900	Single	3.1	-	-	-	24	4.2	140
FQB3N90	900	Single	4.25	-	-	-	20	3.6	130
FQB2NA90	900	Single	5.8	-	-	-	15	2.8	107
FQB2N90	900	Single	7.2	-	-	-	12	2.2	85
TO-263(D²PAK) P-Channel									
FQB3P50	-500	Single	4.9	-	-	-	18	2.7	85
FQB1P50	-500	Single	10.5	-	-	-	11	1.5	63
FQB4P40	-400	Single	3.1	-	-	-	18	3.5	85
FQB2P40	-400	Single	6.5	-	-	-	10	2	63
FQB9P25	-250	Single	0.62	-	-	-	29	9.4	120
SFW9644	-250	Single	0.8	-	-	-	45	8.6	123
FQB6P25	-250	Single	1.1	-	-	-	21	6	90
FQB4P25	-250	Single	2.1	-	-	-	10	4	75
SFW9624	-250	Single	2.4	-	-	-	16	2.7	38
FQB2P25	-250	Single	4	-	-	-	6.5	2.3	52

Products	BV _{DSS} Min (V)	Configuration	R _{DS(ON)} Max. (Ohms) @ V _{GS} =				Q _g (nC) Typ @ V _{GS} = 5V (Note pg. i)	Maximum Rating	
			10V	4.5V	2.5V	1.8V		I _D (A)	P _D (W)
TO-263(D²PAK) P-Channel (cont.)									
SFW9614	-250	Single	4	-	-	-	9	1.6	20
FQB12P20	-200	Single	0.47	-	-	-	31	11.5	120
RF1S9640SM	-200	Single	Use FQB12P20						
SFW9640	-200	Single	0.5	-	-	-	46	11	123
FQB7P20	-200	Single	0.69	-	-	-	19	7.3	90
SFW9630	-200	Single	0.8	-	-	-	29	6.5	70
FQB5P20	-200	Single	1.4	-	-	-	10	4.8	75
SFW9620	-200	Single	1.5	-	-	-	15	3.5	38
FQB3P20	-200	Single	2.7	-	-	-	6	2.8	52
SFW9610	-200	Single	3	-	-	-	9	1.8	20
FQB22P10	-100	Single	0.125	-	-	-	40	22	125
FQB17P10	-100	Single	0.19	-	-	-	30	16.5	100
SFW9540	-100	Single	0.2	-	-	-	43	17	132
FQB12P10	-100	Single	0.29	-	-	-	21	11.5	75
SFW9530	-100	Single	0.3	-	-	-	30	10.5	66
FQB8P10	-100	Single	0.53	-	-	-	12	8	65
SFW9520	-100	Single	0.6	-	-	-	16	6	49
FQB5P10	-100	Single	1.05	-	-	-	6.3	4.5	40
SFW9510	-100	Single	1.2	-	-	-	9	3.6	32
FQB27P06	-60	Single	0.07	-	-	-	33	27	120
FQB17P06	-60	Single	0.12	-	-	-	21	17	79
SFW9Z34	-60	Single	0.14	-	-	-	30	18	82
FQB11P06	-60	Single	0.175	-	-	-	13	11.4	53
SFW9Z24	-60	Single	0.28	-	-	-	15	9.7	49
SFW2955	-60	Single	0.3	-	-	-	15	9.4	49
FQB7P06	-60	Single	0.41	-	-	-	6.3	7	45
SFW9Z14	-60	Single	0.5	-	-	-	9	6.7	38
FDB6021P	-20	Single	-	0.03	0.04	0.065	20	28	37
NDB6020P	-20	Single	-	0.05	0.075	0.07@2.7V	25	24	60
FDB4020P	-20	Single	-	0.08	0.11		9.5	16	37.5
TO-220F N-Channel									
FQPF85N06	60	Single	0.01	-	-	-	86	53	62
FQPF65N06	60	Single	0.016	-	-	-	48	40	56
FQPF50N06L	60	Single	0.021	0.025@5V		-	24.5	32.6	47
FQPF50N06	60	Single	0.022	-	-	-	31	31	47
FQPF30N06L	60	Single	0.035	0.045@5V		-	15	22.5	38
FQPF30N06	60	Single	0.04	-	-	-	19	21	39
FQPF20N06L	60	Single	0.055	0.07@5V		-	9.5	15.7	30
FQPF20N06	60	Single	0.06	-	-	-	11.5	15	30
FQPF13N06L	60	Single	0.11	0.14@5V		-	4.8	10	24
FQPF13N06	60	Single	0.135	-	-	-	5.8	9.4	24
FQPF90N08	80	Single	0.016	-	-	-	84	44	62
FQPF70N08	80	Single	0.017	-	-	-	75	43.6	60
FQPF58N08	80	Single	0.024	-	-	-	50	35	55
FQPF44N08	80	Single	0.034	-	-	-	38	25	41
FQPF17N08L	80	Single	0.1	0.115@5V		-	8.8	11.2	30
FQPF17N08	80	Single	0.115	-	-	-	12	11.2	30
FQPF9N08	80	Single	0.21	-	-	-	5.9	7	23
FQPF9N08L	80	Single	0.21	0.23@5V		-	4.7	7	23
SSS70N10A	100	Single	0.023	-	-	-	151	28	49
FQPF70N10	100	Single	0.025	-	-	-	85	35	62
FQPF55N10	100	Single	0.026	-	-	-	75	34.2	60
FQPF44N10	100	Single	0.039	-	-	-	48	27	55
IRFS550A	100	Single	0.04	-	-	-	75	21	46

Products	BV _{DSS} Min (V)	Configuration	R _{DS(ON)} Max. (Ohms) @ V _{GS} =				Q _g (nC) Typ @ V _{GS} = 5V (Note pg. i)	Maximum Rating	
			10V	4.5V	2.5V	1.8V		I _D (A)	P _D (W)
TO-220F N-Channel (cont.)									
FQPF33N10	100	Single	0.052	-	-	-	38	18	41
IRFS540A	100	Single	0.052	-	-	-	60	17	39
FQPF33N10L	100	Single	0.052	0.055@5V	-	-	30	18	41
IRLS540A	100	Single	-	0.058@5V	-	-	38.4	17	44
FQPF19N10	100	Single	0.1	-	-	-	19	13.6	38
FQPF19N10L	100	Single	0.1	0.11@5V	-	-	14	13.6	38
IRLS530A	100	Single	-	0.12@5V	-	-	16.9	10.7	36
IRFS530A	100	Single	0.11	-	-	-	27	10.7	32
FQPF13N10	100	Single	0.18	-	-	-	12	8.7	30
FQPF13N10L	100	Single	0.18	0.2@5V	-	-	8.7	8.7	30
IRLS520A	100	Single	-	0.22@5V	-	-	10.2	7.2	30
IRFS520A	100	Single	0.2	-	-	-	16	7.2	28
FQPF7N10	100	Single	0.35	-	-	-	5.8	5.5	23
FQPF7N10L	100	Single	0.35	0.38@5V	-	-	4.6	5.5	23
IRLS510A	100	Single	-	0.44@5V	-	-	5.5	4.5	23
IRFS510A	100	Single	0.4	-	-	-	8.5	4.5	21
FQPF46N15	150	Single	0.042	-	-	-	85	25.6	66
FQPF28N15	150	Single	0.09	-	-	-	40	16.7	60
FQPF9N15	150	Single	0.4	-	-	-	10	6.9	44
FQPF6N15	150	Single	0.6	-	-	-	6.5	5	38
FQPF5N15	150	Single	0.8	-	-	-	5.4	4.2	32
SSS45N20B	200	Single	0.065	-	-	-	133	20	57
FQPF34N20	200	Single	0.075	-	-	-	60	17.5	55
FQPF34N20L	200	Single	0.075	0.08@5V	-	-	55	17.5	55
IRFS650B	200	Single	0.085	-	-	-	95	28	50
FQPF18N20V2	200	Single	0.14	-	-	-	20	18	40
FQPF19N20L	200	Single	0.14	0.15@5V	-	-	27	12.8	50
IRLS640A	200	Single	-	0.18@5V	-	-	40	9.8	40
FQPF19N20	200	Single	0.15	-	-	-	31	11.8	50
IRFS640B	200	Single	0.18	-	-	-	45	18	43
FQPF12N20	200	Single	0.28	-	-	-	18	8.2	45
FQPF12N20L	200	Single	0.28	0.32@5V	-	-	16	8.2	45
IRLS630A	200	Single	-	0.4@5V	-	-	18.6	6.5	36
FQPF10N20	200	Single	0.36	-	-	-	13.5	6.8	40
FQPF10N20C	200	Single	0.36	-	-	-	20	9.5	38
FQPF630	200	Single	0.4	-	-	-	19	6.3	38
IRFS630B	200	Single	0.4	-	-	-	22	9	38
FQPF7N20	200	Single	0.69	-	-	-	8	4.8	37
FQPF7N20L	200	Single	0.75	0.78@5V	-	-	6.8	5	37
IRLS620A	200	Single	-	0.8@5V	-	-	10.3	4.1	26
IRFS620B	200	Single	0.8	-	-	-	12	5	32
FQPF5N20	200	Single	1.2	-	-	-	6	3.5	32
FQPF5N20L	200	Single	1.2	1.25@5V	-	-	4.8	3.5	32
FQPF4N20L	200	Single	1.35	1.4@5V	-	-	4	3	27
FQPF4N20	200	Single	1.4	-	-	-	5	2.8	27
IRFS610B	200	Single	1.5	-	-	-	7.2	3.3	22
FQPF27N25	250	Single	0.11	-	-	-	50	14	55
IRFS654B	250	Single	0.14	-	-	-	95	15	50
FQPF16N25	250	Single	0.23	-	-	-	27	9.5	50
IRFS644B	250	Single	0.28	-	-	-	47	14	43
FQPF9N25	250	Single	0.42	-	-	-	15.5	6.7	45
IRFS634B	250	Single	0.45	-	-	-	29	8.1	38
FQPF6N25	250	Single	1	-	-	-	6.6	4	37
IRFS624B	250	Single	1.1	-	-	-	13.5	4.1	34
FQPF4N25	250	Single	1.75	-	-	-	4.3	2.8	32

Products	BV _{DSS} Min (V)	Configuration	R _{DS(ON)} Max. (Ohms) @ V _{GS} =				Q _g (nC) Typ @ V _{GS} = 5V (Note pg. i)	Maximum Rating	
			10V	4.5V	2.5V	1.8V		I _D (A)	P _D (W)
TO-220F N-Channel (cont.)									
IRFS614B	250	Single	2	-	-	-	8.1	2.8	22
FQPF3N25	250	Single	2.2	-	-	-	4	2.3	27
FQPF22N30	300	Single	0.16	-	-	-	47	12	56
FQPF14N30	300	Single	0.29	-	-	-	30	8.5	50
FQPF9N30	300	Single	0.45	-	-	-	17	6	42
FQPF5N30	300	Single	0.9	-	-	-	9.8	3.9	35
FQPF3N30	300	Single	2.2	-	-	-	5.5	2	20
FQPF2N30	300	Single	3.7	-	-	-	3.7	2.1	40
FQPF17N40	400	Single	0.27	-	-	-	45	9.5	56
IRFS750A	400	Single	0.3	-	-	-	101	8.4	49
FQPF11N40	400	Single	0.48	-	-	-	27	6.6	50
IRFS740B	400	Single	0.54	-	-	-	41	10	44
FQPF7N40	400	Single	0.8	-	-	-	16.5	4.6	42
FQPF6N40C	400	Single	1	-	-	-	16	6	38
IRFS730B	400	Single	1	-	-	-	25	5.5	38
FQPF5N40	400	Single	1.6	-	-	-	10	3	35
IRFS720B	400	Single	1.75	-	-	-	14	3.3	33
FQPF3N40	400	Single	3.4	-	-	-	6	1.6	20
IRFS710B	400	Single	3.4	-	-	-	7.7	2	23
FQPF2N40	400	Single	5.8	-	-	-	4	1.1	16
FQPF18N50V2	500	Single	0.265	-	-	-	42	18	69
FQPF13N50	500	Single	0.43	-	-	-	45	7.3	56
FQPF13N50C	500	Single	0.48	-	-	-	43	13	48
FQPF9N50	500	Single	0.73	-	-	-	28	5.3	50
FQPF9N50C	500	Single	0.8	-	-	-	28	9	44
IRFS840B	500	Single	0.85	-	-	-	41	8	44
FQPF6N50	500	Single	1.3	-	-	-	17	3.6	42
FQPF5N50C	500	Single	1.4	-	-	-	18	5	38
IRFS830B	500	Single	1.5	-	-	-	27	4.5	38
FQPF5N50	500	Single	1.8	-	-	-	13	3	39
IRFS820B	500	Single	2.6	-	-	-	14	2.5	33
FQPF4N50	500	Single	2.7	-	-	-	10	2.3	35
FQPF2N50	500	Single	5.3	-	-	-	6	1.3	20
SSS1N50B	500	Single	5.5	-	-	-	8.3	1.2	23
FQPF1N50	500	Single	9	-	-	-	4	0.9	16
FQPF12N60C	600	Single	0.65	-	-	-	48	12	51
FQPF12N60	600	Single	0.7	-	-	-	42	5.8	55
FQPF10N60C	600	Single	0.73	-	-	-	44	9.5	50
SSS10N60B	600	Single	0.8	-	-	-	54	9	50
FQPF7N60	600	Single	1	-	-	-	29	4.3	48
FQPF8N60C	600	Single	1.2	-	-	-	28	7.5	48
SSS7N60B	600	Single	1.2	-	-	-	38	7	48
FQPF6N60	600	Single	1.5	-	-	-	20	3.6	44
FQPF5N60	600	Single	2	-	-	-	16	2.8	40
FQPF4N60	600	Single	2.2	-	-	-	15	2.6	36
SSS4N60B	600	Single	2.5	-	-	-	22	4	33
FQPF3N60	600	Single	3.6	-	-	-	10	2	34
FQPF2N60	600	Single	4.7	-	-	-	9	1.6	28
SSS2N60B	600	Single	5	-	-	-	12.5	2	23
FQPF1N60	600	Single	11.5	-	-	-	5	0.9	21
SSS1N60B	600	Single	12	-	-	-	5.9	1	17
FQPF6N70	700	Single	1.5	-	-	-	30	3.5	48
SSS6N70A	700	Single	1.8	-	-	-	51	4	40
FQPF2N70	700	Single	6.3	-	-	-	8.1	2	28
FQPF8N80C	800	Single	1.55	-	-	-	35	8	59

Products	BV _{DSS} Min (V)	Configuration	R _{DS(ON)} Max. (Ohms) @ V _{GS} =				Q _g (nC) Typ @ V _{GS} = 5V (Note pg. i)	Maximum Rating	
			10V	4.5V	2.5V	1.8V		I _D (A)	P _D (W)
TO-220F N-Channel (cont.)									
FQPF7N80C	800	Single	1.9	-	-	-	27	6.6	56
FQPF6N80	800	Single	1.95	-	-	-	31	3.3	51
FQPF6N80C	800	Single	2.5	-	-	-	21	5.5	51
FQPF5N80	800	Single	2.6	-	-	-	25	2.8	47
FQPF4N80	800	Single	3.6	-	-	-	19	2.2	43
FQPF3N80C	800	Single	4.8	-	-	-	13	3	39
FQPF3N80	800	Single	5	-	-	-	15	1.8	39
FQPF2N80	800	Single	6.3	-	-	-	12	1.5	35
FQPF5N90	900	Single	2.3	-	-	-	31	3	51
FQPF6N90C	900	Single	2.3	-	-	-	30	6	56
FQPF4N90	900	Single	3.1	-	-	-	24	2.5	47
FQPF4N90C	900	Single	4.2	-	-	-	17	4	47
FQPF3N90	900	Single	4.25	-	-	-	20	2.1	43
FQPF2NA90	900	Single	5.8	-	-	-	15	1.7	39
FQPF2N90	900	Single	7.2	-	-	-	12	1.4	35
TO-220F P-Channel									
FQPF3P50	-500	Single	4.9	-	-	-	18	1.9	39
FQPF1P50	-500	Single	10.5	-	-	-	11	1	28
FQPF4P40	-400	Single	3.1	-	-	-	18	2.4	39
FQPF2P40	-400	Single	6.5	-	-	-	10	1.3	28
FQPF9P25	-250	Single	0.62	-	-	-	29	6	50
SFS9644	-250	Single	0.8	-	-	-	45	4.9	40
FQPF6P25	-250	Single	1.1	-	-	-	21	4.2	45
SFS9634	-250	Single	1.3	-	-	-	29	3.4	33
FQPF4P25	-250	Single	2.1	-	-	-	10	2.8	38
SFS9624	-250	Single	2.4	-	-	-	16	2.4	28
FQPF2P25	-250	Single	4	-	-	-	6.5	1.8	32
SFS9614	-250	Single	4	-	-	-	9	1.3	13
FQPF12P20	-200	Single	0.47	-	-	-	31	7.3	50
SFS9640	-200	Single	0.5	-	-	-	46	6.2	40
FQPF7P20	-200	Single	0.69	-	-	-	19	5.2	45
SFS9630	-200	Single	0.8	-	-	-	29	4.4	33
FQPF5P20	-200	Single	1.4	-	-	-	10	3.4	38
SFS9620	-200	Single	1.5	-	-	-	15	3	28
FQPF3P20	-200	Single	2.7	-	-	-	6	2.2	32
SFS9610	-200	Single	3	-	-	-	9	1.4	13
FQPF22P10	-100	Single	0.125	-	-	-	40	13.2	45
FQPF17P10	-100	Single	0.19	-	-	-	30	10.5	41
SFS9540	-100	Single	0.2	-	-	-	43	10.7	53
FQPF12P10	-100	Single	0.29	-	-	-	21	8.2	38
SFS9530	-100	Single	0.3	-	-	-	30	8	39
FQPF8P10	-100	Single	0.53	-	-	-	12	5.3	28
SFS9520	-100	Single	0.6	-	-	-	16	4.6	29
FQPF5P10	-100	Single	1.05	-	-	-	6.3	2.9	23
SFS9510	-100	Single	1.2	-	-	-	9	2.5	16
FQPF47P06	-60	Single	0.026	-	-	-	84	30	62
FQPF27P06	-60	Single	0.07	-	-	-	33	17	47
FQPF17P06	-60	Single	0.12	-	-	-	21	12	39
SFS9Z34	-60	Single	0.14	-	-	-	30	12	36
FQPF11P06	-60	Single	0.175	-	-	-	13	8.6	30
SFS9Z24	-60	Single	0.28	-	-	-	15	7.5	29
SFS2955	-60	Single	0.3	-	-	-	15	7.3	29
FQPF7P06	-60	Single	0.41	-	-	-	6.3	5.3	24
SFS9Z14	-60	Single	0.5	-	-	-	9	5.3	24

Products	BV _{DSS} Min (V)	Configuration	R _{DS(ON)} Max. (Ohms) @ V _{GS} =				Q _g (nC) Typ @ V _{GS} = 5V (Note pg. i)	Maximum Rating	
			10V	4.5V	2.5V	1.8V		I _D (A)	P _D (W)
TO-247 N-Channel									
HUF75345G3	55	Single	0.007	-	-	-	125	75	325
HUFA75345G3	55	Single	0.007	-	-	-	125	75	325
HUF75344G3	55	Single	0.008	-	-	-	90	75	285
HUFA75344G3	55	Single	0.008	-	-	-	90	75	285
HUF75343G3	55	Single	0.009	-	-	-	92	75	270
HUFA75343G3	55	Single	0.009	-	-	-	92	75	270
HUF75339G3	55	Single	0.012	-	-	-	60	75	200
HUFA75339G3	55	Single	0.012	-	-	-	60	75	200
HUFA75337G3	55	Single	0.014	-	-	-	51	75	175
HUFA75333G3	55	Single	0.016	-	-	-	40	66	145
HUFA75332G3	55	Single	0.019	-	-	-	40	60	145
HUFA75329G3	55	Single	0.024	-	-	-	35	49	128
FDH038AN08A1	75	Single	0.0038	-	-	-	125	80	450
HUF75652G3	100	Single	0.008	-	-	-	211	75	515
HUFA75652G3	100	Single	0.008	-	-	-	211	75	515
HUF75639G3	100	Single	0.025	-	-	-	57	56	200
HUFA75639G3	100	Single	0.025	-	-	-	57	56	200
IRFP150N	100	Single	0.03	-	-	-	90	44	155
IRFP140N	100	Single	0.04	-	-	-	35	33	120
HUF75852G3	150	Single	0.016	-	-	-	215	75	500
HUFA75852G3	150	Single	0.016	-	-	-	215	75	500
HUF75945G3	200	Single	0.071	-	-	-	118	38	310
FDH34N40	400	Single	0.115	-	-	-	57	34	469
FDH44N50	500	Single	0.12	-	-	-	90	44	625
FDH40N50F	500	Single	0.13	-	-	-	85	42	625
FDH27N50	500	Single	0.19	-	-	-	56	27	450
FDH15N50	500	Single	0.38	-	-	-	33	15	250
TO-3P N-Channel									
FQA170N06	60	Single	0.0056	-	-	-	220	170	375
FQA85N06	60	Single	0.01	-	-	-	86	100	214
FQA65N06	60	Single	0.016	-	-	-	48	72	183
FQA160N08	80	Single	0.007	-	-	-	220	160	375
FQA90N08	80	Single	0.016	-	-	-	84	90	214
FQA70N08	80	Single	0.017	-	-	-	75	77	190
FQA58N08	80	Single	0.024	-	-	-	50	64	180
FQA44N08	80	Single	0.034	-	-	-	38	49.8	163
FQA140N10	100	Single	0.01	-	-	-	220	140	375
SSH70N10A	100	Single	0.023	-	-	-	151	70	300
FQA70N10	100	Single	0.025	-	-	-	85	70	214
FQA55N10	100	Single	0.026	-	-	-	75	61	190
FQA44N10	100	Single	0.039	-	-	-	48	48	180
IRFP150A	100	Single	0.04	-	-	-	75	43	193
FQA33N10	100	Single	0.052	-	-	-	38	36	163
IRFP140A	100	Single	0.052	-	-	-	60	31	131
FQA33N10L	100	Single	0.052	0.055@5V	-	-	30	36	163
FQA90N15	150	Single	0.018	-	-	-	220	90	375
FQA70N15	150	Single	0.028	-	-	-	135	70	330
FQA46N15	150	Single	0.042	-	-	-	85	50	250
SFH154	150	Single	0.075	-	-	-	90	34	204
FQA28N15	150	Single	0.09	-	-	-	40	33	227
FQA65N20	200	Single	0.032	-	-	-	170	65	310
FQA48N20	200	Single	0.05	-	-	-	100	48	280
SSH45N20B	200	Single	0.065	-	-	-	133	45	278
FQA34N20	200	Single	0.075	-	-	-	60	34	210
FQA34N20L	200	Single	0.075	0.08@5V	-	-	55	34	210

Products	BV _{DSS} Min (V)	Configuration	R _{DS(ON)} Max. (Ohms) @ V _{GS} =				Q _g (nC) Typ @ V _{GS} = 5V (Note pg. i)	Maximum Rating	
			10V	4.5V	2.5V	1.8V		I _D (A)	P _D (W)
TO-3P N-Channel (cont.)									
IRFP250B	200	Single	0.085	-	-	-	95	32	204
FQA19N20L	200	Single	0.14	0.15@5V	-	-	27	25	190
FQA19N20	200	Single	0.15	-	-	-	31	23	190
IRFP240B	200	Single	0.18	-	-	-	45	20	180
FQA55N25	250	Single	0.04	-	-	-	140	55	310
FQA40N25	250	Single	0.07	-	-	-	85	40	280
FQA34N25	250	Single	0.085	-	-	-	60	34	245
FQA27N25	250	Single	0.11	-	-	-	50	27	210
IRFP254B	250	Single	0.14	-	-	-	95	25	221
FQA16N25	250	Single	0.23	-	-	-	27	18.5	190
IRFP244B	250	Single	0.28	-	-	-	47	16	180
FQA44N30	300	Single	0.069	-	-	-	120	43.5	310
FQA38N30	300	Single	0.085	-	-	-	90	38.4	290
FQA22N30	300	Single	0.16	-	-	-	47	22	190
FQA14N30	300	Single	0.29	-	-	-	30	15	160
FQA35N40	400	Single	0.105	-	-	-	110	35	310
FQA30N40	400	Single	0.14	-	-	-	90	30	290
FQA20N40	400	Single	0.22	-	-	-	60	19.5	200
FQA17N40	400	Single	0.27	-	-	-	45	17.2	190
IRFP350A	400	Single	0.3	-	-	-	101	17	202
FQA11N40	400	Single	0.48	-	-	-	27	11.8	160
IRFP340B	400	Single	0.54	-	-	-	41	11	162
FQA28N50	500	Single	0.16	-	-	-	110	28.4	310
FQA28N50F	500	Single	0.16	-	-	-	110	28.4	310
FQA24N50	500	Single	0.2	-	-	-	90	24	290
FQA24N50F	500	Single	0.2	-	-	-	90	24	290
IRFP460C	500	Single	0.24	-	-	-	87	14	205
SSH22N50A	500	Single	0.25	-	-	-	182	22	278
FQA18N50V2	500	Single	0.265	-	-	-	42	20	227
FQA16N50	500	Single	0.32	-	-	-	17	16	200
IRFP450B	500	Single	0.4	-	-	-	87	14	205
FQA13N50	500	Single	0.43	-	-	-	45	13.4	190
FQA9N50	500	Single	0.73	-	-	-	28	9.6	160
IRFP440B	500	Single	0.85	-	-	-	41	8.5	162
FQA24N60	600	Single	0.24	-	-	-	110	23.5	310
FQA19N60	600	Single	0.38	-	-	-	70	18.5	300
FQA12N60	600	Single	0.7	-	-	-	42	12	240
SSH10N60B	600	Single	0.8	-	-	-	54	10	193
FQA7N60	600	Single	1	-	-	-	29	7.7	152
SSH7N60B	600	Single	1.2	-	-	-	38	7.3	160
FQA6N70	700	Single	1.5	-	-	-	30	6.4	152
FQA13N80	800	Single	0.75	-	-	-	68	12.6	300
FQA10N80C	800	Single	1.1	-	-	-	44	10	240
FQA8N80C	800	Single	1.55	-	-	-	35	8.4	220
FQA7N80C	800	Single	1.9	-	-	-	27	7	198
FQA6N80	800	Single	1.95	-	-	-	31	6.3	185
FQA11N90	900	Single	0.96	-	-	-	72	11.4	300
FQA11N90C	900	Single	1.1	-	-	-	60	11	300
FQA8N90C	900	Single	1.1	-	-	-	35	8	240
FQA9N90C	900	Single	1.4	-	-	-	45	9	280
FQA5N90	900	Single	2.3	-	-	-	31	5.8	185
FQA6N90C	900	Single	2.3	-	-	-	30	6	198
TO-3P P-Channel									
FQA9P25	-250	Single	0.62	-	-	-	29	10.5	150
SFH9244	-250	Single	0.8	-	-	-	45	8.7	126

Products	BV _{DSS} Min (V)	Configuration	R _{DS(ON)} Max. (Ohms) @ V _{GS} =				Q _g (nC) Typ @ V _{GS} = 5V (Note pg. i)	Maximum Rating	
			10V	4.5V	2.5V	1.8V		I _D (A)	P _D (W)
TO-3P P-Channel (cont.)									
SFH9250L	-200	Single	-	0.23@5V	-	-	90	19.5	204
FQA12P20	-200	Single	0.47	-	-	-	31	12.6	150
SFH9240	-200	Single	0.5	-	-	-	46	11	126
SFH9154	-150	Single	0.2	-	-	-	100	18	204
FQA22P10	-100	Single	0.125	-	-	-	40	24	150
TO-3PF N-Channel									
FQA17P10	-100	Single	0.19	-	-	-	30	18	120
SFH9140	-100	Single	0.2	-	-	-	43	19	166
FQA47P06	-60	Single	0.026	-	-	-	84	55	214
FQAF85N06	60	Single	0.01	-	-	-	86	67	100
FQAF65N06	60	Single	0.016	-	-	-	48	49	86
FQAF90N08	80	Single	0.016	-	-	-	84	56	100
FQAF70N08	80	Single	0.017	-	-	-	75	53	90
FQAF58N08	80	Single	0.024	-	-	-	50	44	85
FQAF44N08	80	Single	0.034	-	-	-	38	35.6	83
FQAF70N10	100	Single	0.025	-	-	-	85	45	100
FQAF44N10	100	Single	0.039	-	-	-	48	33	85
IRFS150A	100	Single	0.04	-	-	-	75	31	100
FQAF33N10	100	Single	0.052	-	-	-	38	25.8	83
IRFS140A	100	Single	0.052	-	-	-	60	23	72
FQAF33N10L	100	Single	0.052	0.055@5V	-	-	30	25.8	83
FQAF70N15	150	Single	0.028	-	-	-	135	44	130
FQAF28N15	150	Single	0.09	-	-	-	40	22	102
SSF45N20B	200	Single	0.065	-	-	-	133	26.4	100
FQAF34N20	200	Single	0.075	-	-	-	60	23	95
FQAF34N20L	200	Single	0.075	0.08@5V	-	-	55	23	95
IRFS250B	200	Single	0.085	-	-	-	95	21.3	90
FQAF19N20L	200	Single	0.14	0.15@5V	-	-	27	16	85
FQAF19N20	200	Single	0.15	-	-	-	31	15	85
IRFS240B	200	Single	0.18	-	-	-	45	12.8	73
FQAF40N25	250	Single	0.07	-	-	-	85	24	108
FQAF34N25	250	Single	0.085	-	-	-	60	21.7	100
IRFS254B	250	Single	0.14	-	-	-	95	16	90
FQAF16N25	250	Single	0.23	-	-	-	27	12.4	85
IRFS244B	250	Single	0.28	-	-	-	47	10.2	73
FQAF14N30	300	Single	0.29	-	-	-	30	11.4	90
SSF25N40A	400	Single	0.2	-	-	-	140	14.3	100
FQAF17N40	400	Single	0.27	-	-	-	45	12.2	100
IRFS350A	400	Single	0.3	-	-	-	101	11.5	92
FQAF11N40	400	Single	0.48	-	-	-	27	8.8	90
IRFS340B	400	Single	0.54	-	-	-	41	8	85
FQAF16N50	500	Single	0.32	-	-	-	17	11.3	110
IRFS450B	500	Single	0.4	-	-	-	87	9.6	96
FQAF13N50	500	Single	0.43	-	-	-	45	9.6	100
FQAF9N50	500	Single	0.73	-	-	-	28	7.2	90
IRFS440B	500	Single	0.85	-	-	-	41	6.2	85
FQAF19N60	600	Single	0.38	-	-	-	70	11.2	120
SSF17N60A	600	Single	0.45	-	-	-	128	9	100
FQAF12N60	600	Single	0.7	-	-	-	42	7.8	100
SSF10N60B	600	Single	0.8	-	-	-	54	6.9	90
SSF7N60B	600	Single	1.2	-	-	-	38	5.4	86
FQAF15N70	700	Single	0.56	-	-	-	70	9.5	120
FQAF6N70	700	Single	1.5	-	-	-	30	4.7	83
FQAF13N80	800	Single	0.75	-	-	-	68	8	120
FQAF8N80	800	Single	1.2	-	-	-	44	5.9	107

Products	BV _{DSS} Min (V)	Configuration	R _{DS(ON)} Max. (Ohms) @ V _{GS} =				Q _g (nC) Typ @ V _{GS} = 5V (Note pg. i)	Maximum Rating	
			10V	4.5V	2.5V	1.8V		I _D (A)	P _D (W)
TO-3PF N-Channel (cont.)									
FQAF6N80	800	Single	1.95	-	-	-	31	4.4	90
FQAF11N90	900	Single	0.96	-	-	-	72	7.2	120
FQAF5N90	900	Single	2.3	-	-	-	31	4.1	90
TO-3PF P-Channel									
FQAF9P25	-250	Single	0.62	-	-	-	29	7.1	70
SFF9244	-250	Single	0.8	-	-	-	45	6	60
SFF9250L	-200	Single	-	0.23@5V	-	-	90	12.6	90
FQAF12P20	-200	Single	0.47	-	-	-	31	11.5	70
SFF9240	-200	Single	0.5	-	-	-	46	7.6	60
FQAF22P10	-100	Single	0.125	-	-	-	40	16.6	70
FQAF17P10	-100	Single	0.19	-	-	-	30	12.4	56
SFF9140	-100	Single	0.2	-	-	-	43	13	80
FQAF47P06	-60	Single	0.026	-	-	-	84	38	100
TO-264 N-Channel									
FQL50N40	400	Single	0.075	-	-	-	160	50	460
FQL40N50	500	Single	0.11	-	-	-	155	40	460
FQL40N50F	500	Single	0.11	-	-	-	155	40	460

Special Function Products

Application Specific

Products	Function	Polarity	Configuration	Operating Voltage Range		I _{LOAD} (typ) (A)	t _{rise} (typ) (us)	t _{fall} (typ) (us)	P _D (W)
				V _{DD} (min)	V _{DD} (max)				
SC70-5									
FDG901D	P-Channel Slew Rate Control Driver	P-Channel	Single	2.7	6	0.00012	28	-	0.15
SuperSOT-6/TSOP-6									
FDC6901L	Integrated Driver & Load Switch	P-Channel	Single Integrated	2.7	6	3	124	-	1.6

Load Switches

Products	V _{IN} Max (V)	V _{GS} Max (V)	I _L (A) @ V _{DROP} = 0.2V			R _{ON} Max (Ohm) @ V _{IN} =					
			12V	5V	2.5V	12V	4.5V	3.3V	2.5V	1.8V	
SC70-6 P-Channel											
FDG6331L	8	8	-	-	0.7	-	0.26	-	0.33	0.45	
FDG6323L	8	8	-	0.36	0.27	-	0.55	-	0.75	-	
FDG6324L	20	8	0.36	0.27	-	0.55	0.75	-	-	-	
SuperSOT-6/TSOP-6 P-Channel											
FDC6331L	8	8	-	2.8	2.5	-	0.055	-	0.07	0.1	
FDC6329L	8	8	-	2.8	1.9	-	0.07	-	0.105	-	
FDC6325L	8	8	-	1.5	1	-	0.13	-	0.18	-	
FDC6323L	8	8	-	1	0.67	-	0.2	0.3	-	-	
FDC6332L	8	-	-	-	-	-	0.35	-	0.5	0.75	
FDC6330L	20	20	2.5	1.6	-	0.08	0.125	-	-	-	
FDC6326L	20	20	1.5	1	-	0.125	0.2	-	-	-	
FDC6324L	20	20	1	0.67	-	0.2	0.3	-	-	-	
SuperSOT-8 P-Channel											
FDR8521L	20	20	2.9	1.8	-	0.07	0.115	-	-	-	

MOSFET & Schottky Diode Combo

Products	V _{DS} (V)	I _D (A)	R _{DS(ON)} Max (Ohm)			Q _G		Schottky Diode		P _D (W)
			10V	4.5V	2.5V	(nC)	V _{GS} (V)	V _F (V)	I _F (A)	
SuperSOT-6/TSOP-6 P-Channel										
FDC6392S	-20	2.2	-	0.15	0.2	3.7	4.5	0.45	1	0.96
TSSOP-8 P-Channel										
FDW6923	-20	3.5	-	0.045	0.075	9.7	4.5	0.5	2	1.2
SO-8 N-Channel										
FDFS6N303	30	6	0.035	0.05	-	12	4.5	0.42	3	2
SO-8 P-Channel										
FDFS2P106A	-60	3	0.11	0.14	-	15	10	0.58	2	2
FDFS2P103	-30	5.3	0.059	0.092	-	5.3	5	0.57	1	2
FDFS2P102	-20	3.3	0.125	0.2	-	3.5	4.5	0.58	2	2
FDFS2P102A	-20	3.3	0.125	0.2	-	2.1	5	0.58	2	2
FDFS2P103A	30	5.3	0.059	0.092	-	5.3	-	0.35	0.25	2

For a complete listing of sales representatives and sales offices,
visit www.fairchildsemi.com/cf/sales_contacts/

For datasheets, application
notes, samples and more,
visit www.fairchildsemi.com

Americas

Fairchild Semiconductor
Customer Response Center
7701 Las Colinas Ridge,
Suite 400 Irving, Texas 75063
United States

China

Fairchild Semiconductor
(Shanghai) Company Limited
Beijing Liaison Office 2506,
China Resources Building
No. 8, Jianguomenbei Avenue
Beijing 100005, P.R. China
Tel: 86-10-8519-2060
Fax: 86-10-8519-2061

Fairchild Semiconductor
(Shanghai) Company Limited
Shenzhen Liaison Office
Room 3108, Shun Hing Square
Di Wang Commercial Centre
5002 Shen Nan Road East
Shenzhen 518008, P.R. China
Tel: 86-755-8246-3088
Fax: 86-755-8246-2092

Fairchild Semiconductor
(Shanghai) Company Limited
Puxi Liaison Office
Room 2208, Kerry Centre
No. 1515 Nanjing West Road
Jingan, Shanghai 200040
P.R. China
Tel: 86-21-5298-6262
Fax: 86-21-5298-5118/9

Finland
Fairchild Semiconductor
Itakatu 3 D 213
FIN-00930 Helsinki
Finland
Tel: 358-9-3411266
Fax: 358-9-3411292

France
Fairchild Semiconductor SAS
Immeuble Dublin
2, place Gustave Eiffel
Silic 227
94528 RUNGIS Cedex
France
Tel: 33-1-5634-7210
Fax: 33-1-5634-7211

Germany
Fairchild Semiconductor GmbH
Oskar-von-Miller-Strasse 4e
D-82256 Fürstenfeldbruck
Germany
Tel: 49-8141-6102-0
Fax: 49-8141-6102-100

Hong Kong

Fairchild Semiconductor
Hong Kong Ltd.
19/F, CMG Asia Tower
The Gateway II
15 Canton Road
Tsimshatsui, Kowloon
Hong Kong
Tel: 852-2722-8338
Fax: 852-2722-8383

Italy

Fairchild Semiconductor Srl
Via Carducci, 125
20099 Sesto San Giovanni (MI)
Italy
Tel: 39-02-249111-1
Fax: 39-02-26263424

Japan

Fairchild Semiconductor Japan Ltd.
6F Bancho-Kaikan
12-1 Gobancho, Chiyoda-ku
Tokyo, 102-0076 Japan
Tel: 81-3-5275-8380
Fax: 81-3-5275-8390

Fairchild Semiconductor Japan Ltd.
Osaka Office
Shin-Osaka Meiko Building 8F
4-3-12, Miyahara, Yodogawa-ku
Osaka, 532-0003 Japan
Tel: 81-6-6398-3670
Fax: 81-6-6398-3680

Korea

Fairchild Korea Semiconductor, Ltd.
Bucheon Office
82-3, Dodang-Dong,
Wonmi-Ku, Bucheon,
Gyeonggi-do, 420-711
Korea
Tel: 82-32-680-1000
Fax: 82-32-680-1949

Fairchild Korea Semiconductor, Ltd.
Suwon Office
6th Floor Song-i Building,
976-12, Youngtong-Dong,
Paldal-Ku, Suwon-si,
Gyeonggi-do, 442-470
Korea
Tel: 82-331-205-0291-8
Fax: 82-331-205-3352

Fairchild Korea Semiconductor, Ltd.
Gumi Office
4F Saero-net Building
274-9, Songjeong-dong
Gumi-si, Gyeongsang-buk-Do,
730-090, Korea
Tel: 82-54-457-4111
Fax: 82-54-457-4121

Mexico

Fairchild Semiconductor
Av. Vallarta #6503 Flr. 14
Col. Cd Granjas
Zapopan Jalisco 45010
Mexico
Tel: 52-3-1100017
Fax: 52-3-1101878

Singapore

Fairchild Semiconductor
Asia Pacific Pte. Ltd.
380 Orchard Road
#20-01/03 Shaw House
Singapore 238868
Tel: 65-6836-0936
Fax: 65-6838-0321/3

Sweden

Fairchild Semiconductor
Industrivagen 7
SE-171 48 Solna
Sweden
Tel: 46-8-6515530
Fax: 46-8-6515505

Taiwan

Fairchild Semiconductor
Hong Kong Ltd. Taiwan Branch
18F-A, No.167
Tun Hwa North Road
Taipei 10500, Taiwan
Tel: 886-2-2712-0500
Fax: 886-2-2546-7188

UK

Fairchild Semiconductor Ltd.
Interface House
Interface Business Park
Wootton Bassett
Swindon SN4 8QE
United Kingdom
Tel: 44-1793-856856
Fax: 44-1793-856857



The following are registered and unregistered trademarks Fairchild Semiconductor owns or is authorized to use and is not intended to be an exhaustive list of all such trademarks: ACE™, Across the board. Around the world.™, ActiveArray™, Bottomless™, CoolFET™, CROSSVOLT™, DOME™, EcoSPARK™, E²CMOS™, EnSigna™, FACT™, FACT Quiet Series™, FAST™, FASR™, FRFET™, GlobalOptoisolator™, GTO™, HiSeC™, i²C™, ImpliedDisconnect™, ISOPLANAR™, LittleFET™, MICROCOUPLER™, MicroFET™, MicroPak™, MICROWIRE™, MSX™, MSXPro™, OCX™, OCXPro™, OPTOLOGIC® OPTOPLANAR™, PACMAN™, POP™, Power247™, PowerTrench®, Programmable Active Droop™, QFET®, QS™, QT Optoelectronics™, Quiet Series™, RapidConfigure™, RapidConnect™, SILENT SWITCHER®, SMART START™, SPM™, Stealth™, SuperSOT™-3, SuperSOT™-6, SuperSOT™-8, SyncFET™, The Power Franchise™, TinyLogic®, TINYOPTO™, TruTranslation™, UHC™, UltraFET®, VCX™.

